



Advanced Card Systems Ltd.
Card & Reader Technologies



ACR128

Dual-Interface Reader

A Product Presentation





Rundown

1. Product Overview
2. Product Feature
3. Product Value
4. Product Application
5. Q & A



Product Overview





Product Overview

ACR128 Dual-Interface Reader

Belonging to the Contactless Product Family – an extension to the product line while also supporting Contact interface

Multi-application reader designed to interface with a PC for conventional smart card applications





Product Features





What are the Key Features of ACR128?



Intelligent Support
Hybrid and Combi Cards

Smart Card Interfaces
PICC (Contactless)
SAM, ICC (Contact)

Device Firmware Upgradeable
via RS232 Upgrade Cable

High-Speed Transaction
106 kbps – 848 kbps (Max)

Supported Card Types
ISO 14443 Type A & B
Mifare
ISO 7816 Class A, B

User-Controllable Peripherals
LED
Buzzer

Others/Misc
Power-Saving Modes
Auto PPS (PICC)

Protocols & Standards
ISO 7816 T= 0 & 1 Contact
ISO 14443 Parts 1-4
Contactless
Native T=CL
PCSC and CCID
USB V2.0 (12 Mbps)



Product Features

PC/SC Standard

- A specification that can facilitate the interoperability necessary to allow ICC*/PICC* to be effectively utilized in PC environment
- Offers common PC programming interfaces and control mechanisms, like PC/SC application

*(Integrated Circuits Card)

*(Proximity Integrated Circuit(s) Card)





Product Features

Intelligent Support on Combi and Hybrid Cards

- For Combi Card, if it is inserted into the contact card slot, ICC interface will be used and PICC interface will be disabled, as well as PC/SC Polling function for PICCs.
- For Hybrid Card, if it is inserted into the contact card slot, both ICC and PICC interfaces will be used to access the Hybrid card.

Combi card = ONE IC chip shares two interfaces

Hybrid card = TWO IC chips for two interfaces



Product Features

Power-Saving mode

- Antenna power is only turned on if required
- Most of time the antenna is turned off
- User is able to control the period of time for turning the antenna on/off
- For ACR120, the antenna is always turned on





Product Features

Auto PPS (PICC)

- Whenever a PICC is recognized by the reader
- Change the communication speed between the PCD and PICC by the Maximum Connection Speed
- The Maximum Connection Speed depends on the card types






Product Features

- ACR128U is built based on a more advanced architecture
- Suitable for high speed transactions requirement
- Suitable for highly secure environment



ACR128 Architecture





Product Value





What are the Key Benefits of ACR128?

Save Costs

Single reader provides additional design and cost-saving benefits for systems integrators and card users.

High Security

SAM on board (Contact Interface)

PICC Support

Supports both Type A and B cards

High-Speed Transaction

Baud rate up to 848 Kbps (contactless)

Contemporary Styling & Durability

Easy to replace SAM

Card alignment tray for contactless card

Landing type contact connector

Ease of integration

PCSC interface

Native T=CL support

Ease of Technology (Migration/Upgrade)

Quick and easy migration from contact

to contactless technology

Firmware upgradable





Product Application





In What Areas can We Apply ACR128?



Transportation



Payment System
(ePurse, etc.)



Campus Facility
Management



Electronic Passport
(ICA)



Network Access




Physical Access Control





How to Use ACR128 - Overview

Sample Scenario: Key Diversification





Thank You!!!

More information on:

<http://www.acs.com.hk/acr128.php>

