



Axicon 12700 2D Barcode Verifier



For 2D barcodes and the smaller linear barcodes

Product Summary

The Axicon 12700 2D barcode verifier is one of the 12000 series from Axicon. It is designed to give consistent accurate results on a wide range of both linear and 2D barcodes up to a maximum size of 71mm x 50mm (including light margins). All barcodes are measured to the latest ISO/ANSI and GS1 standards.

With its nominal 5mil aperture that can be adjusted as appropriate to suit the barcode, the Axicon 12700 is suitable for all barcodes with an X dimension greater than 180 microns and up to a maximum physical size of 71mm x 50mm. Suitable for QR Codes, Datamatrix, Aztec, PDF417, MicroPDF as well as a range of linear barcodes.

Accuracy, Repeatability and Reliability.

Axicon have been involved with barcode verification for over 30 years and pioneered the use of CCD imaging for verification. With time comes experience and we're not short of either! Actively listening to our clients suggestions, we constantly enhance and improve our system. The result? The most comprehensive and flexible verification solutions on the market.

Benefits

- ISO/ANSI/GS1 verification standards
- Variable aperture with manual override
- Wide range of print and reporting options
- Easy operation
- PQ Test Kit available for on-site re-certification
- Meets ISO 15415, 15426-2 (and other) standards



Church Road
Weston on the Green,
Oxfordshire,
OX25 3QP, U.K.
Tel +44 (0)1869 351 155
email: sales@axicon.com
www.axicon.com



THE BARCODE EXPERTS



**Solution
Partner**

Axicon 12700 Barcode Verifier



Software Specifications

Symbologies Verified:	DataMatrix, QR Code, Aztec, PDF417, MicroPDF, EAN-8, EAN-13, UPC-E, UPC-A, GS1 Databar, ITF, Code 39, Code 128, MSI Plessey (subject to maximum field of view - see below)
Analysis Performed:	Full ISO/ANSI verification to the latest standards. The system includes free-of-charge software updates for life to enable it to be kept current with the latest standards.
Diagnostics Windows:	Main screen (image of barcode, decode, grade etc), Data Detail, General Characteristics, ISO Quality Parameters and detail, Scan Profile, Report Format.
Reporting:	To PDF, HTML, CSV or Text formats. Includes ability to append to PDF files.
Configurable Options:	Symbology. Application Standard, reporting information, print format and content.

Hardware Specifications

Dimensions:	Base : 148mm x 172mm x 210mm high
Scan area:	71mm x 50mm
Weight:	1.34 kgs (2.95 lbs) - verifier excluding power supply unit
Construction:	Cast Aluminium
Interface:	USB2
Power Consumption:	Current draw from USB2 port: Negligible (connection is for data transfer only) Power supply unit requires input 110 - 240vac 50/60 cycles Output 25W max. (Use only approved power supply - output 12v at 0.8A).
Nominal Measuring Aperture:	5mil The software can be set by the user to the required setting either by aperture selecting a fixed aperture or an automatically adjusted aperture.
Wavelength of Light:	660 nanometres.

General Information

Print of Analysis:	A printed report can be produced on any connected printer.
Standard Accessories:	Transit case, Calibration Sheet, Start-up Guide, Software CD, Compliance Certificates.
System requirements:	PC running Windows XP or later with a USB 2 port available.
Environmental:	Operating Temperature: 10°C to 40°C (50 to 104°F) Storage Temperature: -20°C to 70°C (-4 to 158°F) Relative Humidity: 25% to 80% @ 40 C non-condensing (25% to 80% @ 104°F non-condensing)
Regulatory Approvals:	CE certified, RoSH Compliant. Meets ISO 15415, ISO 15426-2, ISO 15416 & ISO 15426-1 standards
Warranty:	1 Year parts and labour - return to bench.

All Trademarks are acknowledged as belonging to their respective companies.

Due to Axicon's continuing product improvement programs, specifications and features herein are subject to change without notice.



axicon
THE BARCODE EXPERTS

Church Road
Weston on the Green,
Oxfordshire, OX25 3QP, U.K.
Tel +44 (0)1869 351 155
email: sales@axicon.com
www.axicon.com