


Specifications

Card Speed: 10 ips (25,40cm/sec) typical	Card Types: Smart cards per ISO 7816; magnetic stripe cards per ISO 7810, 7811, 7813; including AAMVA and California Driver's Licenses
MTBF: Electronics: 125,000 hours Head: 1,000,000 passes Smart Card Contacts: 1,000,000 insertions	Accept Embossed Cards: Per ISO 7811-1/3
Input Voltage: 12.0 VDC \pm 5%	Dimensions (Core Chassis): Length (with "A" bezel): 5.85 in. (152,24mm) Width (with "A" bezel): 3.26 in. (82,8mm) Height (with "A" bezel): 2.17 in. (55,14mm) Interface cable length: 6 ft. \pm 0.1 ft. (1,83m \pm 0,03m) Power adaptor cable length: 6.25 ft. (1,91m)
Current: 1.5 amp max.	Weight: Reader with "A" bezel: 15.33 oz. (434,68gr) I/O cable: 4.15 oz. (117,76gr) SAM ranch with cable: 2.90 oz. (82,24gr) AC adaptor regulator w/power cord: 11.87 oz. (336,6gr)
Audible Noise: 55db at 39.4" (1,0m)	
Card Travel Time: 400 ms \pm 20% maximum input or eject time	
Read Capabilities: Tracks 1, 2, 3; Lo-Co or Hi-Co, 100% of magnetic stripe	
Interface: RS-232	


Standard Configurations

IntelliStripe 350		IntelliStripe 320	
3 Track, RS-232,		3 Track, RS-232, "A" bezel:	16050326
extended "C" bezel w/LED:	16050340	3 Track, RS-232, extended "C" bezel w/LED:	16050328
I/O cable DB9	16051412	3 Track, RS-232, w/flush mount "D" bezel:	16050329
Power adaptor (110-240 volt)	64300080	I/O cable DB9	16051408
		Power adaptor (110-240 volt)	64300080
		USA power cord	71100001

IntelliStripe 350



IntelliStripe 320



MAGTEK


20725 S. Annalee Avenue
 Carson, CA 90746
 Phone: (310) 631-8602
 Fax: (310) 631-3956

Internet: <http://www.magtek.com>

1-888-624-8350

MAGTEK

IntelliStripe 320 & 350




Hybrid Motorized Reader

Magnetic Stripe • Smart Card



Your migration path to smart card...

- EMVCo Certified
- Supports ISO 7816 T=0 & T=1 microprocessor cards
- Supports most popular memory cards
- Supports high speed smart card interface with transfer data rates of up to 115Kbps
- Intelligent, RS-232 interface
- Single socket on-board Security Access Module (SAM)
- Built in interface port for optional SAM ranch which supports smart card
- 8 contacts per ISO
- Reads up to three tracks of magnetic stripe data
- Optional security gate and coin guard
- Power-fail card-eject electronics
- FLASH programmable
- Rugged, zinc die-cast chassis



IntelliStripe 320


Shown with D bezel, stripe down

- Clean design
- Short footprint
- Versatile card orientation
- Compatible with many ATMs
- No LED

IntelliStripe 320

Shown with C bezel, stripe down

- Extended bezel features integrated graphics showing correct card orientation
- LED visual indicator
- Easy card alignment



IntelliStripe 350

Desktop model with C bezel, stripe down

- For use in over-the-counter application where magstripe and/or smart card technologies are used such as car rental agencies and hotels