

Product profile

PB_{22/32/50}

Rugged Mobile Label Printers



- The industry's fastest 2, 3, and 4 inch rugged mobile label printers
- Built rugged to survive real-world industrial and retail environments
- Two to three times faster time-to-first-label than competitive products
- Low cost of development, deployment and support
- Seamless integration with Intermec mobile computers and other mobile devices
- Secure wired and wireless communications options: Bluetooth®, 802.11 b/g, USB, Serial
- Label sensors minimize printing errors and reduce waste
- SmartSystems® remote device management reduces support needs
- Optimized for Intermec media, including linerless label media options

The Intermec rugged mobile label printer family delivers the fastest choice for customers with demanding applications in warehousing, distribution, in-store retail and enterprise asset management. Coupled with Intermec rugged mobile computers and software, the PB22, PB32 and PB50 mobile label printers help companies improve productivity and efficiency while lowering the total cost of ownership.

With ultra-fast print speed and proven two to three times faster time-to-first-label* than competitive products, these printers deliver measurable improvements in worker productivity and accuracy. Unique design elements, such as the label gap and label take sensors, help maintain productivity while reducing waste.

The PB label printer family is built on a common electrical and mechanical foundation, and integrates closely with Intermec mobile computers and software, including Intermec Terminal Emulation (ITE) and Intermec SmartSystems®. This integrated approach provides significant efficiencies in development, deployment and support, and optimizes speed and performance. Intermec SmartSystems provides remote monitoring and diagnostics to networked devices so problems can be resolved quickly.

Shared accessories across the family add flexibility and reduce spares inventory and costs. Intermec media options, designed specifically for the PB printers, ensure consistently high print quality across a range of applications.

Leveraging the Intermec platform gives companies a solution that can adapt and grow with their needs. As "smart" printers, the rugged PB printers can host stand-alone applications developed through Intermec Fingerprint programming to address custom requirements today or in the future, without the need to upgrade hardware.

The printers' comprehensive options and easy adaptability meet a range of application needs. Drop-in media loading, adjustable media holders, and the flexibility to print either receipts or labels enables workers to easily change tasks without changing equipment. A choice of secure wired and wireless interfaces (802.11 b/g, BT, Serial, USB) allows you to select the one that fits your environment. Multiple carrying options are available, including belt clip, shoulder strap and vehicle mount.

The rugged design of the PB22, PB32 and PB50 printers means performance you can depend on, day after day.

Built to thrive in the same environment as Intermec computers, the printers have a 5 foot multiple drop spec, IP54 seal rating, and forklift-strength shock and vibration specs, minimizing repairs and downtime. When issues do arise, Intermec Medallion Complete service contracts deliver peace-of-mind and insurance against unbudgeted repair costs.

Physical Characteristics

PB22:

Width: 101 mm (4 in)
Height: 176 mm (6.9 in)
Depth: 71 mm (2.8 in)
Weight (with battery): 678 g (23.9oz)

PB32:

Width: 127 mm (5 in)
Height: 182 mm (7.2 in)
Depth: 81 mm (3.2 in)
Weight (with battery): 828 g (29.2oz)

PB50:

Width: 160 mm (6.3 in)
Height: 174.5 mm (6.9 in)
Depth: 78.8 mm (3.1 in)
Weight (with battery): 1189 g (42.0 oz)

Environment

Operating temperature: -15°C to 50°C (5°F to 122°F)
Storage temperature: -30°C to 70°C (-22°F to 158°F)
Humidity: 10 to 90% (non-condensing)
Sealing: IP54 (excludes paper path)
Drop spec: 1.5m (5 ft.) drops to concrete; 26 times including all corners and sides
PB22/ 32: 2m (6.5 ft) multiple drops to concrete with optional protective case

Power

PB22/ 32: 7.2V Li-Ion, 2.25 Ah, rechargeable battery
PB50: 14.8V Li-Ion, 2.2 Ah, rechargeable battery

Memory

RAM: 16MB
Flash: 64MB

Standard Communications

RS-232 Serial
USB v.2.0

Optional Communications

Bluetooth® (v2.0, Class 1)
802.11b/g

Wireless Security

Authentication & Encryption Options:

WEP (64 and 128 bit) LEAP; WPA-PSK (TKIP/ RC4); WPA2/ 802.11i-PSK (CCMP/ AES); EAP-TLS, -TTLS, -PEAP, -FAST

Print Speed and Resolution

4ips (101.6mm/ sec)
203 dpi (8 dots/ mm)

Print Technology

Printhead: Direct thermal

Media

Type: Labels or receipt media

Intermec Media:

Labels and Tags: Duratherm II, Duratherm III, Duratherm NIR, Duratherm III IR, Duratherm III Synthetic, Duratherm III Linerless, Duratherm II 5-mil Tag

Receipts: Duratherm Receipt II, Duratherm Receipt III

Media Width Ranges:

PB22: 25.4mm to 55.88mm (1 to 2.2 in)
PB32: 30.48mm to 83.82mm (1.2 to 3.3 in)
PB50: 49mm to 111.5mm (2 to 4.39 in)

Core ID: 19mm (0.75 in) standard, 10.16 mm (0.4 in) supported

Max OD:

PB22: 57.2mm (2.25 in)
PB32: 67.3mm (2.65 in)
PB50: 67.3mm (2.65 in)

Software

Programming Languages:

IPL, Fingerprint, ZSim (ZPLII Simulation), ESC-P, DSim (DPL), CSim (CPCL)

Character Sets

Standard: English and Latin

Optional: Western European, ASCII, CodePage 850, Central European, Cyrillic, Latin, Greek, Turkish, Hebrew, Arabic, Baltic, Baltic RIM, Vietnamese, Thai, Simplified Chinese, Traditional Chinese, Korean, UTF-8

Graphics

Supports user-defined fonts, graphics, formats and layouts, including custom logos.

Barcode Symbologies

All major 1D and 2D symbologies are supported.

User Interface

LCD and 4 buttons: standby, paper feed, setup, infoFour audio status indicators: error alert, hardware change alert, button press alert and startup alert.

Accessories

Hand strap, shoulder strap, belt clip, protective case, cart mount, vehicle mount, battery pack, four-bay battery charger, A/C adapter, A/C power cord, truck power cable adapter, truck power cable, forklift power cable, serial cable

Safety Approvals

North America: UL and cUL Listed, UL 60950-1

Europe: D Mark, EN 60950-1; CE marked

Mexico: NYCE Certified, NOM 19

Other Countries: IEC 60950-1

EMC Approvals

USA FCC Title 47, Part 15, Subpart B, Class B; Europe EMC Directive (EN55022 Class B + EN55024) ; CISPR22

Warranty

One year; additional Medallion service packages available


SmartSystems™

Asia Pacific Headquarters Office

Singapore

Intermec Technologies (S) Pte Ltd
151, Lorong Chuan,
#05-02A/03 (Lobby C),
New Tech Park,
Singapore 556741
Tel : +65 6303 2100
Fax: +65 6303 2199
www.intermec.com.sg

Malaysia

Suite L-8-11, Level-8, Wisma BU8,
No 11, Lebuhr Bandar Utama, PJU 6,
Petaling Jaya, 47800,
Selangor,
Malaysia
Tel : +603 7726 8730
Fax: +603 7727 8731

Thailand

Two Pacific Place,
Unit 1105,
142 Sukhumvit Road,
Klongtoey, Bangkok 10110,
Thailand
Tel : +662 653 2750
Fax: +662 653 2751

Australia

Intermec Technologies Australia
Pty. Ltd.
Level 4, 1-3 Atchison Street,
St. Leonards, NSW 2065,
Australia
Tel : +61 2 9330 4400
Fax: +61 2 9437 0240
www.intermec.com.au

Korea

Hong-Eun B/D Room 902,
824-22, Yeoksam-dong,
Gangnam-gu,
Seoul 135-934,
Korea
Tel : +82 2 552 2484
Fax: +82 2 552 2483

Hong Kong

Rm 3601 11/F,
AXA Centre,
151 Gloucester Road,
Wanchai,
Hong Kong
Tel : 852.3752 1906
Fax: 852.3013 9401

China

Beijing

1510A, 15th floor, South Tower,
Raycom Infotech Park C,
No.2 Science Institute South Road,
Beijing, 100190,
P.R. China
Tel : +86 10 5165 5922
Fax: +86 10 6583 4408

Shanghai

Unit B3, Floor 28, No. 789,
Zhaojiangbang Road,
JuneYao International Plaza,
Shanghai 200032,
P.R. China
Tel : +86 21.6278 1090
Fax: +86 21.6278 1081

Shenzhen

Unit 1308, International
Chamber of Commerce Tower
Fu Hua Third Road,
Fu Tian Central District,
Shenzhen 518048, P.R. China
Tel : +86 755.8831 2391
Fax: +86 755.8831 2396

China Toll Free: 400 6100 277
www.intermec.com.cn

Copyright © 2011 Intermec Technologies Corporation.
All rights reserved. Intermec is a registered trademark
of Intermec Technologies Corporation. All other
trademarks are the property of their respective owners.
Printed by MG Digital Corp-013 02/11.

In a continuing effort to improve our products, Intermec
Technologies (S) Pte Ltd reserves the right to change
specifications and features without prior notice.

