

Description

- 111 Mechanical key switches with tactile feeling
- Numeric Keys included
- 10 million operating life cycles
- Standard Key Code or ASCII Code configuration support
- Simple-Programming key function via software
- Optional Integrated Magnetic Stripe Card Reader (MSR) available with dual/triple track combinations
- Program up to 200 characters or codes per key
- Multi-Layer Programming Capability: Up to 16 layers



Specification

| Key Layout | 111 Keys |
|--|---|
| Key Type | Mechanical |
| Key Travel | 4mm ± 0.5 mm |
| Life Cycle | 10 million operations |
| Indicator | 3 LED Indicators |
| Interface | PS/2 |
| Key Configuration | Multiple Keys programmable (Key code or ASCII code) |
| Integrated Magnetic Card Reader (optional) | |
| Standard | Comply with ISO 7812, IBM standards, American Driving License |
| Card Density | Track 1: 210BPI with max. 76 characters Track 2: 75BPI with max. 37 characters Track 3: 210BPI with max. 107 characters |
| Magnetic Track | Track 1 or Track 2 or Track 3 Dual Track (Track 1&2 or Track 2&3) Three Track (Track 1&2&3) |
| Reading Speed | 10 to 100 cm/sec. |
| Reading Cycle | 30,000 or 1,000,000 (Option) |
| General | |
| Power Input | 5VDC ± 10% |
| OS Support | Windows-base (98/Me/2000/XP/Vista 32-bit) |
| Weight | 1,800 g |
| Dimension (L x W x H: mm) | 380 x 175.08 x 47.25 |
| Cable Length | 2.8 m |