



# POS-1000

## Fanless Full Flat Touch Screen POS Terminal

- Energy-Saving Atom D2550 (Dual Core 1.86 GHz)
- DDR3 RAM Module (up to 4GB)
- 15 inch Full-Flat LCD monitor
- Touch Screen: 5-Wire Resistive
- Fanless Cooling System
- Optional Rear Mount VFD Customer Display
- Secondary Display (10.4 inch, Touchscreen Type Available)
- Optional Compact MSR Module
- I/O Interface: USB 2.0 / RS-232 / RJ-11 / RJ-45...etc.
- Compact Base Design Ideal for Small Workplace Operation



More Info



15 inch Full-flat Touch Screen



MSR Module



Rear Mount VFD Display



10.4" Secondary LCD Display



Easy HDD replacement



Sleek & Compact Design





## Specifications

POS-1000	
<b>Main Board</b>	
CPU	Intel Atom D2550 Dual Core (1.86 GHz, 1M Cache)
Chipset	NM10
System Memory	1 x 204 pin DDR3 SO-DIMM Socket, up to 4GB
Graphic	Intel D2550 integrated, Share System Memory
OS Support	POS Ready 2009, POS Ready 7, Windows 7, Windows 8.1, Linux
<b>Display</b>	
Display Type	15" Full Flat LCD Monitor
Brightness	250 nits
Resolution	1024 x 768 pixels
Touch Screen	5 Wire Resistive Type
Tilting Angle	15-80 Degrees (up to 90 degree possible)
<b>Storage</b>	
HDD	1 x 2.5" SATA
Auxiliary Storage	1 x mSATA
<b>Interface</b>	
Serial	2 x COM with Power Selected 5/12V, 1 x RJ45
USB	5 x USB2.0 (External),
PS/2	1 x PS/2 (for PS/2 Keyboard/Mouse)
LAN	1 x RJ-45, Giga LAN Support
VGA	1 x DB-15, Female
DC Out	1 x 12VDC Jack for Customer Display or 2nd LCD Display
Cash Drawer	1 x RJ-11, 12/ 24 VDC Selectable
Audio Jack	1 x Line Out, 1 x MIC In, 2 x Internal Speaker 2W
<b>Other</b>	
Power Input	12VDC 90W, 4-pin Connector with Lock (External Adaptor: 100~240 VAC, 50/60HZ)
Color	White, Black, Orange
Dimensions (mm)	323 x 230 x 344
Weight	5.0 Kg
Certificate	FCC / CE / WEEE / RoHS
Operating Temperature	0°C-40°C
Operating Humidity	20% - 80% RH non-condensing
Storage Temperature	-20°C-60°C
Storage Humidity	20%-85% RH non-condensing