



POS-6000

Fanless Full Flat Touch Screen POS Terminal

- DDR 3 RAM Module (1~8GB)
- Fanless Cooling System
- Easy HDD Replacement
- Rear Mount VFD Customer Display
- Embedded MSR & i-Button
- Bay Trail Celeron J1900 (Quad, 2.0GHz)
- 15 inch Projective Capacitive Full-flat LCD Monitor
- Interface: USB 2.0/RS-232/RJ-11/RJ-45...etc.
- Internal Cable Routing Base Ideal for Small Workplace Operation



More Info



Full-flat Touch Screen



Secondary LCD Display



Sturdy Aluminum Base



Easy HDD Replacement



Power Adaptor Hidden Under Base



Concealed Cable Routing





Specifications

	POS-6000-D2550	POS-6000-B	POS-6000-I
Main Board			
CPU	Intel Atom D2550 Dual Core (1.86 GHz, 1M Cache)	Bay Trail-D Platform, Celeron® J1900 (2.0 GHz, 2M Cache)	Core i7 3630QM , 2.4GHz (6M Cache, up to 3.40 GHz) Core i5 3320M , 2.6GHz (3M Cache, up to 3.30 GHz) Core i3 3120M , 2.5GHz (3M Cache, 2.50 GHz) Celeron B810 (2M Cache, 1.6 GHz)
Chipset	NM10	---	Intel QM77
System Memory	1 x 204 pin DDR3 SO-DIMM Socket, up to 4GB	1 x DDR3 SO-DIMM 1333MHz, up to 8 GB	2 x 204 pin DDR3 SODIMM Socket, up to 16GB
Graphic	Intel D2550 integrated, Share System Memory	Intel® HD Graphics	Intel HD Graphics 4000, Share System Memory
OS Support	POS Ready 2009, POS Ready 7, XP Pro, Vista, Windows 7, Linux		
Display			
Display Type	15" Full Flat LCD Monitor		
Brightness	250 nits		
Resolution	1024 x 768 pixels		
Touch Screen	5 Wire Resistive Type or Projective Capacitive		
Tilting Angle	15-80 Degrees		
Storage			
HDD	1 x 2.5" SATA for HDD or SSD	1 x 2.5" SATA for HDD or SSD	1 x 2.5" SATA for HDD or SSD
Auxiliary Storage	1 x mSATA	1 x CFast Slot	1 x CFast Slot
Interface			
Serial	3 x COM with Power Selected 5/12V (COM 1/2/6), 1 x COM without Power Output (COM 4) Select by Jumper	4 x COM (DB9, with COM 1/COM 2 power output, +5VDC/+12VDC, selectable by Jumper)	4 x COM (3 x DB9, 1 x RJ45, with power output, 5/ 12V selectable)
Parallel	---		
USB	5 x USB 2.0 (External), 3 x USB 2.0 (Internal, reserved for touch screen, Wi-Fi, and MSR)	1 x USB 3.0 (External), 4 x USB 2.0 (External, 2 x bottom/ 2 x side)	2 x USB3.0 (External), 4 x USB2.0 (External), 3 x USB2.0 (Internal, reserved for touch screen, Wi-Fi, and MSR)
PS/2	1x mixed PS/2 (for mouse or keyboard)	1 x PS/2 (for PS/2 Keyboard/Mouse)	1x mixed PS/2 (for mouse or keyboard)
LAN	1 x RJ-45, Giga LAN Support		
VGA	1 x DB-15, Female		
DC Out	1 x 12VDC Jack for Customer Display or 2nd Display		
Cash Drawer	1 x RJ-11, 12/ 24 VDC Selectable		
Audio Jack	1 x Line Out, 1 x MIC In, 1 x Internal Speaker 2W		
Other			
Power Input	12VDC 90W, 4-pin Connector with Lock (External Adaptor: 100-240 VAC, 50/60HZ)		
Color	Silver, Black, White		
Dimensions (mm)	391.2 x 245.0 x 352.3		
Weight	6.7 Kg		
Certificate	FCC / CE / WEEE / RoHS		
Operating Temperature	0°C-40°C		
Operating Humidity	20% - 80% RH non-condensing		
Storage Temperature	-20°C-60°C		
Storage Humidity	20% -85% RH non-condensing		