



Introduction

SGT-662 touch screen monitor is the industries grade touch screen monitor comes with strong solid base. Ideal for industry and F&B application. SGT662 come with 1024x768 resolutions on 15 inch screen. Resist to heavy duty touch environment. The adjustable stand for your SGT662 allows 25° forward or 30° backward tilt to maximize your viewing comfort.

FEATURES:

- High resolution: Support 1024*768
- Grade A LCD panel;
- 5 wires touch panel for option with water-proof;
- Lifetime: 50 million touch;
- Designed for comfort
- Affordable and highly reliable
- Energy-efficient design

SPECIFICATION:

LCD Screen Size	15"
Aspect Ratio	4:3
Resolution	1024×768
Pixel Pitch(mm)	0.297
Active Area(mm)	304.1×228.1
Number of colors	16.2M
Contrast Ratio	700/1
Brightness	250cd/m ²
Viewing Angle	150/135
Response Time	8ms
Touch Panel Size	15" 5-wire
Outside Dimension	247mm×322mm
Viewing area	235mm×310mm
Active area	228mm×304mm
Surface Hardness	3H
Optical Clarity	80%

Operating Temperature	-10C ~60C
Endurance Test strikes	Over 10millions
Operating Voltage	DC5V
Resistance	200Ω~900Ω
Linearity	1.50%
Faceplate Surface	Anti-glare coating,glare coating
Film Thickness	0.175mm, 0.188mm
Glass Thickness	0.7mm, 1.1mm,1.8mm
Operation Pressure	20~150g
Storage Temperature	-30°C~80 °C
Operating Current	5mA~25mA
Humidity	<95%
Isolation Resistance	20MΩ @DC25V
Sealable against	Dust ,water, oil , static

