



Description:

Features:

Direct thermal printing method, Quick and efficient printing, Rugged design withstands drops up to 1.2 meter. Long lasting Lithium-ion battery (7.4V, 2100mAh), Easy drop-in clamshell paper loading, Support a wide variety of serial and wireless communication options, Continue printing when battery in charging, Easy to store setup parameters by Setup Tools

Specifications:

Print	Printing Method	Direct Thermal
	Printing Speed	60mm/s(average), 80mm/s(max)
	Resolution	8 dots/mm, 576 dots/line (203dpi)
	Effective Printing Width	72mm
Character	Character Set	ASCII,GB2312-80(Chinese)
	Print Font	ANK: 12 x24 Chinese: 24 x 24
	Character per Line	48
Paper Spec	Paper Type	Thermal paper
	Paper Width	80±0.5mm or 76±0.5mm
	Paper Roll Diameter	Max: 60.0mm
	Roll Core Inner Diameter	13mm(min.)
	Paper Thickness	0.06 to 0.07mm
Paper Supply Method		Drop-in Easy loading
Reliability	MCBF	15 million lines
	TPH	100km
Barcodes		EAN-13, EAN-8, UPC-A, UPC-E, CODE39, CODE93, CODE128, CODABAR, INTERLEAVED 25
Emulation		ESC/POS
Sensor		Paper End Sensor
Interface		T8-BT:RS-232,Bluetooth
Power Adaptor		DC12V/2A
Battery Power		DC7.4V, 2.1A rechargeable Li-ion battery
Battery duration		2300 receipts or 230m continuous printing
Physical	Weight	516g(excluding roll paper)
	Dimension (WxLxH)	120 x153 x80mm
	Color	Black