



Description:

Features:

Light weight for true mobility, Pocket size 102 x 77 x 36mm, Direct thermal printing method
Easy to use and simple to maintain, Easy drop-in clamshell paper loading, Support RS232, IrDA, and Bluetooth interface, Continuing printing when battery in charging.

Specifications:

Print	Printing Method	Direct Thermal
	Printing Speed	50mm/s(average), 65mm/s(max)
	Resolution	8 dots/mm, 384 dots/line
	Effective Printing Width	48mm
Character	Character Set	ASCII,GB2312-80(Chinese)
	Print Font	ANK: 12 x24 Chinese: 24 x 24
	Character per Line	32/42
Paper Spec	Paper Type	Thermal paper
	Paper Width	57.5± 0.5mm
	Paper Roll Diameter	Max: 40.0mm
	Roll Core Inner Diameter	13mm(min.)
	Paper Thickness	0.06 to 0.07mm
Paper Supply Method		Drop-in Easy loading
Reliability	MCBF	15 million lines
	TPH	50km
Barcodes		EAN-13, EAN-8, UPC-A, UPC-E, CODE39, CODE93, CODE128, CODABAR, INTERLEAVED 25
Emulation		ESC/POS
Sensor		Paper End Sensor
Interface		TIII-BT:RS-232,Bluetooth; TIII-Ir:RS-232, IrDA;
Power Adaptor		DC9V/2A
Battery Power		DC7.4V,1.5A rechargeable Li-ion battery
Battery duration		100m continuous printing
Physical	Weight	275g(Including battery & roll paper)
	Dimension (WxLxH)	102 x 77 x36mm
	Color	Beige