

# Facestock

A white, one side	gloss finished	cast coated paper.
Basis Weight	80 g/m²	ISO 536
Caliper	88 µm	ISO 534

# Adhesive

S1010 is an emulsion acrylic adhesive with best in class initial tack and ultimate adhesion on high surface energy substrates.

# Liner

BG40 is a high-density glassine paper featuring high internal strength, toughness and tear resistance as well as high transparency.

Basis Weight	57 g/m²	ISO 536
Caliper	51 µm	ISO 534

# Laminate

Total Caliper 154 µm ± 10% Calculated

# **Typical Performance Data**

Initial Tack 12.0 N/25mm Peel Adhes. 90° 9.0 N/25mm Min. appl. temp. 5°C

FTM 2 st.st.

FTM 9 glass

Service temp. -20°C to 80°C subject to facestock limitations

\*Typical Performance Data only serves as reference to product performance under specified testing conditions and does not represent a product specification. Customers are recommended to test under actual conditions of use to determine its suitability. Temperature data shown only applies to adhesive test performance.

# Applications and Use


This product is suitable for wide range of promotional and industrial labels whereby excellent gloss appearance and attractive multi-colour print quality are required. S1010 adhesive has been developed to give optimum "price-performance" factor to its end-users. It adheres well to a number of substrates. For applications that require better performing adhesive, Fasson® higher performance paper adhesive such as S2090 is recommended. Typical applications include labels for cosmetic, food products and promotional labels.

#### **Conversion/Printing**

This glossy, cast coated quality is specially suited to provide top printing quality in all usual printing techniques, whether single or multi-colour, line or process colour printing. High internal strength of the glassine liner provides excellent support for die cutting both rotary and flat bed.

# AW0271

# Fasson<sup>®</sup> High Gloss Paper/S1010/ BG40Wh Imp FSC



High Gloss Paper	
S1010	
BG40Wh Imp FSC	

# Food Industry Labels

The adhesive complies with FDA regulations (section 175.105) for indirect food contact.

#### Statement of Practical Use

As with all pressure sensitive materials, this product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.

#### Shelf life

To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT ( $20-25^{\circ}C$ ; 40-50% RH). Prolonged storage outside these conditions might reduce the shelf life.

Note: The information in this datasheet is correct at time of publishing. Avery Dennison reserves the right to revise the content as required without prior notice.

Thailand	Malaysia	Indonesia	Vietnam	Myanmar	Singapore	Philippines

Warranty

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. AVERY DENNISON products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Any product shown to the satisfaction of AVERY DENNISON within the time provided to be so defective shall be replaced without charge of AVERY DENNISON may issue credit in such amount as it seems reasonable however, in no event shall AVERY DENNISON be responsible for claims beyond the replacement value of the defective product or in any way liable or responsible for consequential or incidental damages. NO EXPRESS WARRANTIES, WHETHER OF MERCHANTABILITY OR FITNESS FOR ANY ARTICULAR USE, OR OTHERWISE, EXCEPT AS SET FORTH ABOVE (WHICH IS MADE EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES) SHALL APPLY TO PRODUCTS SOLD BY AVERY DENNISON. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN EXECUTIVE OFFICER OF AVERY DENNISON. No salesman, representative, or agent of AVERY DENNISON is authorized to give any guarantee, warranty or make any representation contrary to the above.