

Facestock

A bi-axially oriented, matte white polypropylene film with a print receptive top coating, which is suitable for conventional and thermal transfer printing, with good durability.

Basis Weight	59 g/m ²	TAPPI T410
Caliper	75 µm	TAPPI T411

Adhesive

A high performance permanent adhesive featuring good initial tack and ultimate bond strength to a wide range of substrates.

Liner

A super calendered, glassine paper, specially designed for medium to high speed conversion. Designed for accurate kiss / die-cutting.

Basis Weight	57 g/m ²	TAPPI T410
Caliper	51 µm	TAPPI T411

Laminate

Total Caliper	144 µm ±10%	Calculated
---------------	-------------	------------

Typical Performance Data

Initial Tack	480 N/m	FTM 9 glass
Peel Adhes. 90°	230 N/m	FTM 2 st.st.
Min. appl. temp.	0°C	
Service temp.	-40°C to 70°C subject to facestock limitations	

Note: Typical Performance Data only serves as reference to product performance under specified testing conditions and does not represent a product specification. Customers are recommended to test under actual conditions of use to determine its suitability.

Applications and Use

This is an excellent, high performance industrial grade adhesive, featuring high initial tack, ultimate adhesion. S2060 is suitable for use in a wide range of durable labeling application which do not need extremely high temperature resistance.

Conversion/Printing

Fasson® 3 Mil Synthetic Paper gives excellent printing performance in thermal transfer printing as well as conventional printing techniques. The facestock can be printed well with flexographic, letterpress and screen printing techniques. The facestock can also be printed with thermal transfer when matched with the correct ribbon. Therefore, careful selection of ribbon and preliminary testing is essential. In case solvent screen inks are used, please consult your ink manufacturer. Material shows excellent register stability on press and excellent flat bed conversion while rotary and magnetic dies need additional care. Square corners should be avoided.



Note : This is a preliminary datasheet. The information in this datasheet is correct at time of publishing. Avery Dennison reserves the right to revise the content as required without prior notice.

Preliminary Product Datasheet

BW0277

Fasson®

3 Mil Synthetic Paper/S2060/ BG40Wh Imp



Food Industry Labels

The adhesive complies with FDA 175.105 and German recommendations XIV as published by BfR. This adhesive can be used in direct contact with dry and moist, non fatty foodstuffs.

RoHS Statements

RoHS/REGULATION 2002/95/EU The substances listed in article 4 lid 1 of 2002/95/EU (RoHS) are not intentionally used in this product. The concentration limits of these substances will not exceed the set maximum concentration limits as provided in the proposed amendment for 2002/95/EU.

Statement of Practical Use

As with all pressure sensitive materials, this product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.

Shelf Life

One year when stored at 23 ± 2°C and 50 ± 5% RH.

Thailand

110/1 Moo 1 Tumbol
Srisajorakhe Yai
Amphur Bangsaothong
Samutprakarn
10570
Thailand

Malaysia

Lot 6, Jalan P/2 Kawasan
Perusahaan Bangi
43650
Bandar Baru Bangi,
Selangor DE
Malaysia

Indonesia

Kawasan Industri Jababeka
Tahap 7 Blok B No 5,
Desa Wangunharja,
Kecamatan Cikarang Utara,
Kabupaten Bekasi 17550 -
Indonesia

Vietnam

Lot I-11, CN13 Road
Industrial Group 1
Tan Binh Industrial Park
Ward Son Ky
Tan Phu District
Ho Chi Minh City Vietnam

Singapore

5B, Toh Guan Road East,
#05-03, 608829
Singapore

Philippines

Unit 2925
L29 Joy Nostalq Center 17
ADB Avenue
Ortigas Center
Pasig Center 1600
Philippines

Warranty

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. AVERY DENNISON products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Any product shown to the satisfaction of AVERY DENNISON within the time provided to be so defective shall be replaced without charge of AVERY DENNISON may issue credit in such amount as it seems reasonable however, in no event shall AVERY DENNISON be responsible for claims beyond the replacement value of the defective product or in any way liable or responsible for consequential or incidental damages.

NO EXPRESS WARRANTIES, WHETHER OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR USE, OR OTHERWISE, EXCEPT AS SET FORTH ABOVE (WHICH IS MADE EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES) SHALL APPLY TO PRODUCTS SOLD BY AVERY DENNISON. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN EXECUTIVE OFFICER OF AVERY DENNISON. No salesman, representative, or agent of AVERY DENNISON is authorized to give any guarantee, warranty or make any representation contrary to the above.