



ISO PVC CARD TK4100

1) Physical Property and Electronic Performance

Description	64 bits, Read only, RF/ 64 ASK Manchester		
IC types	TK410		
Frequency	125KHz \pm 5KHz		
Reading Distance	,Depending on the reader design and local installation conditions)		
Physical	Thickness	0.96mm	\pm 0.04mm
	Width	53.98mm	\pm 0.05mm
	Length	85.60mm	\pm 0.013mm
	Weight	6.0g	\pm 0.5g
	Color	White/ White	
	Surface	Matt or Glossy	
Printing	Printable with offset, silkscreen, personalizing.		
	Printable with ink Jet numbering (various different format)		
Material	PVC,		
MagStripe	Optional Loco 350 Oe, Hico650 Oe, 2750 Oe and 4000 Oe at ISO position.		
Specials	1. Cards can withstand to static and dynamic curvature and torsion 1000 cycles. These tests are carried out in conformance to ISO 10373-1 standard. Cards is still functional after test. Chip, antenna and connection between antenna and chip can be against any failure.		
	2. Storage: Temperature: 0°C, + 50°C,Relative Humidity 30 at 70 % RH Operation: Temperature: -20°C, + 50°C,Relative Humidity 5 at 95 % RH		

Tatwah technology reserves the rights to change any information or data in this document without prior notice.

Address: No.9, Shuiyi South Road, Taifeng Industrial park, Xiaolan Town, Zhongshan City.Guangdong Province, China, 528415 Tel: +86 760 22108818 /Fax: +86 760 22235000 Email: mango1@vip.163.com



2) Recommendable Operating Conditions

- 2.1 There shall be no metal material or equipment within 50cm.
- 2.2 There shall be no CRTs such as PC or TV that could become a source of noise within 1m.
- 2.3 The usage should be under in normal indoor temperature and humidity.

3) Precautions When Using Product

- 3.1 Do not bend or apply excessive force to the product.
- 3.2 Be careful of the amount of force placed on the product during printing...ect.
- 3.3 In order to preserve stored data,keep product away from magnets.
- 3.4 Do not store product on car dashboards or other locations where the temperature may become very hot.

4) Defective Products

Any products that do not fall within standard specifications due to defects or errors in manufacture will be replaced with properly working ones by following the prescribed product replacement application.

5) Warranty

Product warranty is valid for a period of one year after delivery of the product.

This warranty is not valid in the below events :

- 5.1 Damage or defects due to storage higher than temperatures notes in the spec.
- 5.2 Extended exposure to direct sunlight.water or chemical agents.
- 5.3 The application of excessive force.
- 5.4 Exert the external force excessively on the products and transform the standard structure of product.

6) Change to These Specifications

In the event of that any omissions or errors are discovered in this specification document.we will promptly act to have it corrected.