



Hand held 2D imager scanner

GS500



An ESD safe, high-voltage-tolerance scanner.

The GS500 is an affordable 2D scanner with great performance and high reliability. Perfect for daily use.

- **Reliable voltage tolerance** - 5-14V ensure a longer lifespan.
- **ESD (Electrostatic Discharge) safe** - Built-in ESD IC, 8KV contact
- **Multiple scanning models** - Supports Trigger, Continuous and Presentation scan modes.
- **Screen reading** - Read barcodes from the screens of mobile devices.
- **Connectivity** - Sturdy SR-type cable that supports USB and VCOM.

Diverse Applications



Retail



Logistics



Manufacturing



Library books management



Warehouse management



Clothing industry



Supermarkets



GS500

Hand held 2D imager scanner

Model	GS500				
Scan Pattern	2D Imager (640 x 480 pixel)				
Light Source	Red Led 625 ± 10nm				
Resolution	5 mil				
Depth of Field	EAN13 (13mil): 50-195mm Code 39 (5mil): 50-105mm PDF417 (6.67mil): 35-135mm Data Matrix (10mil): 36-140mm QR Code (15mil): 30-165mm				
Scanning Angle	Skew: 55°, Pitch: 55°, Roll: 360°				
Print Contrast	≥ 30% reflection difference				
Decode Capabilities	EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code128, Code 93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2 Of 5, GS1 DataBar, Code 39, Code 11, MSI/Plessey, Plessey, PDF417, Data Matrix (ECC200, ECC000, 050, 080, 100, 140), QR Code				
Interface	USB 2.0, VCOM				
Dimension (H x W x D)	147mm (5.79") x 66mm (2.60") x 101mm (3.98")				
Weight	130g ± 10 (w/o Cable), 200g ± 10 (W/Cable)				
Color	Black				
Indicators	LED, Beeper				
Input Voltage	DC 5V ± 0.5V				
Current	7 mA (Standby), 230 mA (Operating)				
Power Consumption	760 mW (Max.)				
Environment	<table border="0"> <tr> <td>Operation Temperature</td> <td>-4 °F to 140 °F (-20 °C to 60 °C)</td> </tr> <tr> <td>Storage Temperature</td> <td>-40 °F to 185 °F (-40 °C to 85 °C)</td> </tr> </table>	Operation Temperature	-4 °F to 140 °F (-20 °C to 60 °C)	Storage Temperature	-40 °F to 185 °F (-40 °C to 85 °C)
Operation Temperature	-4 °F to 140 °F (-20 °C to 60 °C)				
Storage Temperature	-40 °F to 185 °F (-40 °C to 85 °C)				
Humidity	5% -95% (non-condensing)				
Light Levels	0 to 100,000 lux				
Drop Resistance	1.5m (4.92 fts) drops to concrete				
Regulatory	CE , FCC , BSMI				

Remark : Specifications are subject to change without notice. All companies and/or product names are trademarks and/or registered trademarks of their respective owners.