

HH400

Handheld 2D Area-Imaging Scanner

HH400 is a mid-to-low range 2D Area-Imaging Scanner, offering outstanding performance at affordable pricing. Being ergonomically designed, this scanner is capable of meeting application requirements in a wide variety of applications. If you are looking for a high-quality, low-cost 2D Area-Imaging Scanner, HH400 would be your best choice.

2D bar codes are becoming increasingly popular in many industry sectors. Examples include QR code on tickets for transportation, club membership bar codes and the bar codes in mobile phones for mobile payment or coupons. HH400 represents the best value-for-money that is capable of not only reading traditional paper-based bar codes but also those on other mediums such as mobile phone screens.

HH400 2D Area-Imaging Scanner stands for an economical and practical choice for enterprises that wish to upgrade their system. Being capable of accurately reading various types of 1D and 2D bar codes, it also supports rapid reading of bar codes on screens. The screen-reading feature makes it an effective data collection device for reading electronic coupons and tickets. HH400 is equipped with advanced engine and scanning-decoding technology. As such it can be used in a wide range of scenarios, making it a foremost choice in industries such as information capturing for electronic ticketing, checking-in and banking applications.



Features



Newly designed 2D image scanning engine: coupled with advanced decoding software for 2D bar codes, HH400 makes it easier to read bar codes. Its long depth-of-field and high-speed 2D bar code scanning ability effectively ensures user experience and operating efficiency.



Reliable world-class design: No movable components for HH400 together with its shock-absorption exterior design ensures sustained working hours, thus reducing the need for incurring additional maintenance cost.



Excellent ergonomic design gives first-class reliability: Optimal gun-shape makes it ideal for sustained handheld scanning operations. Its design also ensures operators' comfort and operating efficiency.



Adapted for future development: HH400's economic and practical 2D bar code scanning function is capable of meeting current and future bar code scanning needs of enterprises.

HH400 Specifications

Mechanical / Electrical

Dimensions (LxWxH): 72.5mmx125mmx154mm

Weight: 125.6g

Input Voltage: 5 ± 0.5VDC

Working Power: 2.0W, 400mA (Typical) @5VDC

Standby power: 0.55W, 110mA (Typical) @5VDC

Interface: USB, RS232

Environmental

Operating temperature: 0 °C ~ 50°C

Storage temperature: -40 °C ~ 60°C

Humidity: 0% ~ 95%

Drop: Designed to withstand 1m drop to concrete

Light levels: 0~70, 000LUX

Scanning Performance

Light source: White LED

Scanner: Red LED, 617nm

Indicator light: Flickering blue light = Decoding successful

Scanning type: Image scanning

Recognizable printing contrast: Minimum 35% contrast

Corner, elevation, drift: ±180°, ±60°, ±70°

Minimum precision: 4mil

Decoding capability: Decodes standard 1D and 2D bar codes; particularly powerful decoding capability for those in screens

Scanning Range

Typical Performance		
Bar Code Density	Near	Far
5 mil Code 39	45mm	100mm
100% UPC/EAN	40mm	250mm
20 mil Code 39	45mm	350mm
20 mil QR Code	35mm	200mm
Minimum precision	4mil	

*Performance may be impacted by bar code quality and environmental conditions

For more information:

www.honeywellaidc.com

Honeywell Safety & Productivity Solutions

9680 Old Bailes Road

Fort Mill, SC 29707

800-582-4263

www.honeywell.com

© 2016 Honeywell International Inc.

Honeywell

www.alcaidc.com