

# HR11+ Aringa

Handheld Barcode Scanner



## Features

### ◆ Value for money.

The HR11+ Aringa is compact & ergonomic in design, maximizing comfort during daily operations. It delivers outstanding scanning performance with a 2500-pixel linear imager and offers an excellent user experience at an affordable price.

### ◆ Ergonomic design.

Blending ergonomics and aesthetics in its design, the HR11+ Aringa ensures operator comfort and productivity for intensive handheld scanning.

### ◆ Scanning from paper and screen.

Equipped with Newland's NLDC technology, the HR11+ Aringa is optimized for fast scanning of 1D barcodes printed on paper or displayed on screen. This makes it a snappy solution for companies looking to tackle emerging applications like O2O.

### ◆ Foldable smart stand available.

A foldable smart stand is available for the HR11+ Aringa, allowing you to quickly switch between hand-held scanning and hands-free scanning.



## Application Scenarios

Retail, O2O, pharmacy, cosmetics & drug stores, smaller sized grocery stores, tobacco kiosks and in a ticketing booth for reading and validating mobile or paper tickets.

# HR11+ Aringa

## Handheld Barcode Scanner

<b>Performance</b>	Image Sensor	2500-pixel linear imager		
	Illumination	Red LED (620nm~630nm)		
	Aiming	Red LED (620nm~630nm)		
	Symbologies	AIM 128, Code 11, Code32, Code 39, Code 93, Code 128, Codabar, COOP 25, Deutsche 12, Deutsche 14, EAN-8, EAN-13, Febraban, GS1-128, GS1 Databar (RSS), ISBN, ISSN, ITF-6, ITF-14, MSI-Plessey, Plessey, UPC-A, UPC-E, Industrial 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, Standard 2 of 5.		
	Resolution*	≥3mil		
	Typical Depth of Field	EAN-13	40mm-480mm (13mil)	
		Code 39	80mm-180mm (5mil)	
	Scan Angle**	Pitch	±60°	
		Skew	±70°	
	Field of view	53°±2°		
	Min. Symbol Contrast	20%		
	Scan Rate	325 scans per second		
	Interfaces	RS-232, USB		
	<b>Physical</b>	Dimensions (L×W×H)	145×101×68mm	
Weight		120g		
Notification		Beep, LED indicator		
Rated Power Consumption		345mW (typical)		
Operating Voltage		5VDC±5%		
Current@5VDC		Operating	70.4mA (typical), 96.8mA (max.)	
		Standby	10mA±1mA	
<b>Environmental</b>		Operating Temperature	-20°C to 60°C	
	Storage Temperature	-40°C to 70°C		
	Humidity	5%~95% (non-condensing)		
	ESD	±8 KV (contact discharge); ±10 KV (air discharge)		
	Drop	1.5m		
	Sealing	IP42		
<b>Certifications</b>	FCC Part15 Class B , CE EMC Class B			
<b>Accessories</b>	Cable	USB	Used to connect the scanner to a host device.	
		RS-232	Used to connect the scanner to a host device.	
	Smart Stand	Used for hands-free scanning.		
	Power Adapter	DC5V adapter, used to power the HR11 with RS-232 cable.		

\*Test conditions: T=23°C; Illumination=300lux using incandescent lamp; sample barcodes made by Newland.

\*\*Test conditions: Scan Distance= (min. DOF + max. DOF)/2; T=23°C; Illumination=300lux using incandescent lamp; 1D: Code 128; 5 Bytes; Resolution=10mil; PCS=0.

\*Specifications are subject to change without notice.\*

**Newland EMEA HQ**  
+31 (0) 345 87 00 33  
info@newland-id.com

**Newland D-A-CH**  
+49 (0) 6182 82916-16  
info@newland-id.de

**Newland France**  
+31 (0) 345 87 00 33  
france@newland-id.com

**Newland Benelux**  
+31 (0) 345 87 00 33  
benelux@newland-id.com

**Newland Ibérica**  
+34 (0) 93 303 74 66  
info@newland-id.es

**Newland Italy**  
+39 (0) 342 056 2227  
italy@newland-id.com

**Newland Nordic & Baltic**  
+46 (0) 708 847 767  
nordic@newland-id.com

**Newland UK**  
+44 (0) 1442 212 020  
sales@newland-id.co.uk

**Newland Russia**  
+31 (0) 345 87 00 33  
russia@newland-id.com

**Newland South Africa**  
+27 (0) 11 553 8010  
info@newland-id.co.za

**Newland Middle East**  
+31 (0) 345 87 00 33  
middleeast@newland-id.com

**Newland Turkey & Iran**  
+90 (0) 544 538 40 49  
turkey@newland-id.com  
iran@newland-id.com