



Heavy-Duty Industrial Barcode Printer for the Most Demanding of Applications



M84PRO Series

INDUSTRY VERTICALS

- "Entry Level" Print & Apply Market
- Manufacturing
- Retail
- Supply Chain

APPLICATIONS

- Bottle & Container Labelling
- Compliance Labelling
- Food Labelling
- Circuit Board Labelling
- Serial Plate Labelling
- Surgical Equipment Labelling
- Diagnostic Kit Labelling

Heavy Duty Industrial Construction ▶

Powerful Memory ▶

Easy Connectivity ▶

Option of Increasing Print Resolution ▶

**Allows Users to Switch Print Resolution
Simply by Changing Printheads** ▶

Windows™ Compatible ▶



General Specifications

M84PRO



| PRINTER MODEL | | M84Pro-2 | M84Pro-3 | M84Pro-6 |
|--------------------------------------|---------------------|---|---------------------|---------------------|
| PRINTING SPECIFICATIONS | | | | |
| Print Method | | Direct Thermal/Thermal Transfer | | |
| Print Resolution | | 8 dots/mm (203dpi) | 12 dots/mm (305dpi) | 24 dots/mm (609dpi) |
| Max. Print Speed | | 254mm/sec (10ips) | 203mm/sec (8ips) | 152mm/sec (6ips) |
| Max. Print Width | | 104mm (4.1") | | |
| Max. Print Length | | 1249mm (49.21") | 835mm (32.9") | 356mm (14.03") |
| MEDIA SPECIFICATIONS | | | | |
| Sensor Type | | Transmissive sensor for gap, Reflective sensor for I-mark | | |
| Media | | Roll Paper: Max External Diameter 218.4mm (8.6"), Face-in Paper core Internal Diameter 76.2mm (3") Fan Fold Paper: Max Folding Height 110mm (4.33") | | |
| Media Type (Thickness) | | 0.08 to 0.26mm (0.003" to 0.010") | | |
| Media Size | Continuous | Width: 22 to 125mm (0.87" to 4.93"), inclusive backing paper size 25 to 128 mm (0.99" to 5.04") Pitch: 6 to 356mm (0.24" to 14.03"), inclusive backing paper size 9 to 359 mm (0.35" to 14.14") | | |
| | Tear OFF | Width: 22 to 125mm (0.87" to 4.93"), inclusive backing paper size 25 to 128 mm (0.99" to 5.04") Pitch: 16 to 356mm (0.63" to 14.03"), inclusive backing paper size 19 to 359 mm (0.75" to 14.14") | | |
| | Cutter / Dispensing | Width: 22 to 125mm (0.87" to 4.93"), inclusive backing paper size 25 to 128 mm (0.99" to 5.04") Pitch: 30 to 356mm (1.18" to 14.03"), inclusive backing paper size 33 to 359 mm (1.30" to 14.14") | | |
| MEMORY PROCESSING | | | | |
| Memory | | Flash memory 2MB. Expandable memory 4MB | | |
| CPU | | 32 bit RISC | | |
| COMMUNICATION INTERFACES | | | | |
| Plug in Interface Cards | | Serial - RS232C Parallel - IEEE1284 Ethernet - 10/100BaseT Wireless 802.11g RS422/485 | | |
| Others | | USB External Connector Port | | |
| FONTS/BARCODE SYBOLOGIES | | | | |
| Internal Fonts | | XU 5x9 dots, XS 17x17 dots, XM 24x24 dots, XB 48x48 dots, XL 48x48 dots OCR-A 15x22 dots OCR-A 22x33 dots OCR-A 44x66 dots OCR-B 20x24 dots OCR-B 30x36 dots OCR-B 60x72 dots | | |
| Internal Raster Fonts | | CG Times, CG Triumvirate | | |
| Barcodes | 1D Barcode | UPC-A/E, EAN, JAN, CODE 39, CODE 93, CODE 128, UCC/EAN 128, Inter-leaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, NW-7, MSI, Postnet, Bookland | | |
| | 2D Barcode | QRCode, PDF 417, MaxiCode, Data Matrix | | |
| | Character Rotation | 0°, 90°, 180°, 270° rotation | | |
| OPERATING & ENVIRONMENTAL | | | | |
| Power Consumption | | AC 100 / 230V +/- 10% Peak 190VA 130W (Standby 24VA 16W) | | |
| Environment | | Operating Environment: 5 to 40°C / 30 to 80% (with no condensation) Storage Environment: -5 to 60°C / 30 to 90% (with no condensation) | | |
| Dimensions | | (W x D x H): 265 x 435 x 335 mm (10.44" x 17.14" x 13.12") | | |
| Weight | | 18.5kg (standard) | | |
| Regulatory | | VCCI (Class B), FCC (Class B), UL, CUL, CE | | |
| ACCESSORIES & OPTIONS | | | | |
| Options | | Cutter unit, Dispensing unit, Rewinder | | |

For more information about SATO in the Asia Pacific, scan QR code below or [click here](#) to visit our website.

