

# Product Comparison



**MB240T**

## Hardware Specifications

Resolution

203 dpi (8 dots/mm)

<b>Print Method</b>	Direct thermal/Thermal transfer
<b>Display</b>	Color LCD touchscreen with buttons
<b>Hardwire Connectivity</b>	Ethernet GPIO Serial RS-232 USB USB Host
<b>Wireless Connectivity</b>	Bluetooth MFi Wi-Fi
<b>Enterprise Printer Management</b>	TSC Console
<b>Type</b>	Industrial
<b>Max. Print Speed</b>	10 ips (254 mm/s)
<b>Max. Print Width</b>	4.25" (108 mm)
<b>Max. Print Length</b>	1,000" (25,400 mm)
<b>RAM</b>	128 MB SDRAM

<b>Flash</b>	128 MB
<b>Optional Cutter</b>	Regular guillotine cutter (full-cut)

## Media Specifications

<b>Internal Label Capacity</b>	8" (203.2 mm) OD
<b>Max. Media Width</b>	0.8" - 4.7" (20 - 120 mm)
<b>Media Type</b>	Continuous; Die-Cut; Black Mark; Fan-Fold; Notch (Outside Wound)
<b>Max. Ribbon Length</b>	450 Meters
<b>Ribbon Width</b>	1.6" - 4.3" (40 - 110 mm)
<b>Media Core Diameter</b>	1" - 3" (25.4 - 76.2 mm)
<b>Min. Label Length</b>	0.2" (5 mm)
<b>Construction</b>	Die-cast based print mechanism/Metal cover with large clear media view window
<b>Programming Languages</b>	TSPL-EZD