# **MEMOR™ K20-25**

## **ODATALOGIC**

### The smart key-based mobile computer for small and medium business

























### MEMOR™ K20-25 - YOUR DAILY COMPANION WITH BEST-IN-**CLASS SCAN PERFORMANCE**

Datalogic's Memor K20-25 mobile computer is the perfect pocketable business companion for any data capture application, from assisted sales to the shop floor, from back-end receiving to the warehouse. It may be small in size, affordable in price, yet it provides plenty of powerful

Made for those users who prefer the tactile feedback of a smart physical keypad, the Memor K20-25 mobile computer is built around the pulsing heart of Datalogic's Megapixel Halogen™ DE2102-HP scan engine. Best-in-class scanning performance is guaranteed by fully exploiting the power of Datalogic's decoding libraries.

### UP-TO-SPEED PLATFORM WITH THE LATEST ANDROID OS

In the Android world, the access to the latest OS release, equipped with the latest security patches, is quite important even for the smallest

The Memor K20-25 mobile computer brings in the very latest standard for this class of products, with a 2GHz octa-core processing power, and it features Android 13 OS (GMS certified in most regions), upgradable to Android 15. Light weight and comfortable to handle, it provides increased robustness with its IP65 rating and survives drops from 1.5 m / 5 feet.

A full-time daily use up to 10 hours is fully guaranteed thanks to the high capacity 4,850 mAh battery.

### CELLULAR CONNECTIVITY GETS VERY HANDY

Whether your activity is deployed inside your facility or in outdoor yards, the Memor K20-25 provides the connectivity you need: Wi-Fi only or Wi-Fi/4G cellular now available for select countries (data only, 4G not available in North America).

### Memor K20





### Memor K25





### **FEATURES**

- · Ultra-Ergonomic, compact and robust
- 4-inch capacitive multi-touch display with Panda hardened glass
- Android 13, upgradeable A15
- 2 GHz, Octa-core CPU with 4GB RAM / 64GB Flash
- Backlit 24 key keyboard, plus two side scan keys and one programmable side key
- Replaceable 4,850 mAh Li-Polymer Battery
- Ruggedized with drop resistance to 1.5 m / 5 ft to concrete and IP65 sealing
- 4G connectivity (data-only) available for select countries
- Powerful Wi-Fi including the 802.11ac standard
- Bluetooth® v5 short range wireless technology and BLE
- NFC for proximity communications
- Rear camera with auto focus, 13MP with flash LED
- Datalogic's Megapixel Halogen™ DE2102-HP "Firefly" scan engine
- Datalogic's SoftSpot™ technology for innovative triggering through the touch display
- EASEOFCARE Service Plans offer a wide range of options to protect your investment, ensuring maximum productivity and ROI

## FOCY EASE OF CARE



### **INDUSTRY - APPLICATION**

- Inventory
- Assisted sales
- · Access control
- · Price checking
- Shop floor applications · Online order fulfilment

- Manual picking (PTG)
- Order verification
- Inventory
- · Shipping/Receiving

### Manufacturing:

- · Production and quality control
- Inventory management
- Pickina

### Healthcare:

- Pharmacy In-store operations
- Pharmacy/Hospital pharmacy Inventory management
- Pharmacy warehouse/Hospital pharmacy warehouse -Light warehousing
- · Analysis Labs specimen traceability
- · Home healthcare

### **MEMOR™ K20-25**

## TECHNICAL SPECIFICATIONS

WIDEL ECG COLUMN	NUCATIONS	
WIRELESS COMMUNICATIONS		
Local Area Network (WLAN)	IEEE 802.11 ac/a/b/g/n/r/d/e/i/k/v/w; Frequency range: Country dependent, typically 2.4 GHz and 5 GHz bands	
Personal Area Network (WPAN)	Bluetooth wireless technology v5 (Classic Bluetooth wireless technology and BLE)	
NFC Communication	Support for the following standards: ISO14443-4 (type-A, type-B); ISO15693; Mifare; Felica	
WWAN / Cellular	Memor K25 only: EMEA and ROW Configuration: LTE-Advanced / 4G+, UMTS/HSPA+, GSM/GPRS: data-only GSM: B5, B3, B8 UMTS: B1/B5/B8 FDD_LTE:B1//3/7/8/5/20/28/ TDD_LTE:B34/B38/39/40/41(100M)	
Global Positioning System (GPS)	Memor K25 only: Integrated Assisted-GPS (A-GPS) Supported Types: GPS, Galileo, BeiDou, GLONASS	
DECODING CAPABII		
1D / Linear Codes	Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes	
2D Codes	Aztec Code, Data Matrix, HanXin Code, MaxiCode, MicroQR Code, QR Code, EAN/JAN Composites, UPC A/E Composites	
Digital Watermarking	Digimarc Barcodes	
Postal Codes	Australian Post, Japan Post, British Post; China Post; IMB, Korea Post, KIX Code, PLANET, POSTNET, Royal Mail Code (RM4SCC)	
Stacked Codes	Micro-PDF417, MacroPDF, PDF417, GS1 DataBar Composites, GS1 DataBar Expanded Stacked, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional	
ELECTRICAL		
Battery	Removable battery pack 4850 mAh with rechargeable Lithium batteries	
ENVIRONMENTAL		
Drop Resistance	Withstands drops from 1.5 m / 5 ft to concrete according to MIL-STD-810H Device with rubber boot withstands drops from 1.8 m / 6 ft to concrete according to MIL-STD-810H	
Tumbles	Device: exceeds 600 hits at 0.5 m (300 cycle) per IEC 60068-2-32 specification Device with rubber boot exceeds 1000 hits at 0.5 m (500 cycle) per IEC 60068-2-32 specification	
Particulate and Water Sealing	IP65	
Temperature	Operating: -20 a 50°C / da -4 a 122°F Storage/Transport: -30 to 70 °C / -22 to 158 °F	
INTERFACES		
Interfaces	USB-C: High Speed USB 2.0 OTG	
SENSORS		
Accelerometer	3-Axis accelerometer to detect orientation	
Gyroscope	Senses angular velocity	
Magnetometer	e-Compass for direction and orientation detection	
Ambient Light	Auto adjusts display backlight	
Proximity	Auto deactivates display when close to face	

Dimensions  16.6 x 6.9 x 1.7 cm / 6.5 x 2.7 x 0.67 in  4-inch IPS WVGA resolution 800 x 480 LED backlight Touch Screen: 5 points multi-touch capacitive panel of hardened glass  Keys  Backlighted 24 keys keyboard, plus two side scan ke programmable side key  Weight  With Battery: 265 g / 9.4 oz  READING PERFORMANCE  Camera  Resolution: 13 MP; Illumination: LED flash; Lens: Aut  2D Ultra slim area imager (supports 1D / 2D codes) Halogen™ DE2102-HP: Resolution: Megapixel (1280 x 800 pixels) Depth of Field: 4 to 90 cm / 1.6 to 35 in, depending of code density and type Aiming: 650nm VLD; Field of View: 42°H x 26°V  Halogen™ DE2102-HP: 1D Linear: 0.0635 mm / 2.5 mils PDF: 0.0762 mm / 3 mils Data Matrix: 0.152 mm / 6 mils  SAFETY & REGULATORY  Agency Approvals  Environmental Compliance  Complies to EU RoHS  DATALOGIC MOBILITY SUITE - Discover more on: datalogic.github.id  Launcher - to lockdown device to kiosk mode, Enter	eys and one		
LED backlight Touch Screen: 5 points multi-touch capacitive panel of hardened glass  Keys  Backlighted 24 keys keyboard, plus two side scan ke programmable side key  Weight  With Battery: 265 g / 9.4 oz  READING PERFORMANCE  Camera  Resolution: 13 MP; Illumination: LED flash; Lens: Aut 2D Ultra slim area imager (supports 1D / 2D codes) Halogen™ DE2102-HP: Resolution: Megapixel (1280 x 800 pixels) Depth of Field: 4 to 90 cm / 1.6 to 35 in, depending or code density and type Aiming: 650nm VLD; Field of View: 42°H x 26°V  Halogen™ DE2102-HP: 1D Linear: 0.0635 mm / 2.5 mils PDF: 0.0762 mm / 3 mils  SAFETY & REGULATORY  Agency Approvals  The product meets necessary safety and regulatory a for its intended use.  Environmental Compliance  Complies to EU RoHS  SOFTWARE  DATALOGIC MOBILITY SUITE - Discover more on: datalogic.github.id	eys and one		
Keys       Backlighted 24 keys keyboard, plus two side scan ke programmable side key         Weight       With Battery: 265 g / 9.4 oz         READING PERFORMANCE       Resolution: 13 MP; Illumination: LED flash; Lens: Aut 2D Ultra slim area imager (supports 1D / 2D codes) Halogen™ DE2102-HP: Resolution: Megapixel (1280 x 800 pixels) Depth of Field: 4 to 90 cm / 1.6 to 35 in, depending of code density and type Aiming: 650nm VLD; Field of View: 42°H x 26°V         Minimum Element Width       Halogen™ DE2102-HP: 1D Linear: 0.0635 mm / 2.5 mils PDF: 0.0762 mm / 3 mils Data Matrix: 0.152 mm / 6 mils         SAFETY & REGULATORY         Agency Approvals       The product meets necessary safety and regulatory a for its intended use.         Environmental Compliance       Complies to EU RoHS         SOFTWARE         DATALOGIC MOBILITY SUITE - Discover more on: datalogic.github.id	to focus		
Weight       With Battery: 265 g / 9.4 oz         READING PERFORMANCE         Camera       Resolution: 13 MP; Illumination: LED flash; Lens: Aut         2D Ultra slim area imager (supports 1D / 2D codes) Halogen™ DE2102-HP: Resolution: Megapixel (1280 x 800 pixels) Depth of Field: 4 to 90 cm / 1.6 to 35 in, depending or code density and type Aiming: 650nm VLD; Field of View: 42°H x 26°V         Minimum Element Width       Halogen™ DE2102-HP; 1D Linear: 0.0635 mm / 2.5 mills PDF: 0.0762 mm / 3 mils Data Matrix: 0.152 mm / 6 mils         SAFETY & REGULATORY         Agency Approvals       The product meets necessary safety and regulatory a for its intended use.         Environmental Compliance       Complies to EU RoHS         SOFTWARE         DATALOGIC MOBILITY SUITE - Discover more on: datalogic.github.id			
READING PERFORMANCE  Camera  Resolution: 13 MP; Illumination: LED flash; Lens: Aut  2D Ultra slim area imager (supports 1D / 2D codes) Halogen™ DE2102-HP: Resolution: Megapixel (1280 x 800 pixels) Depth of Field: 4 to 90 cm / 1.6 to 35 in, depending of code density and type Aiming: 650nm VLD; Field of View: 42°H x 26°V  Halogen™ DE2102-HP: 1D Linear: 0.0635 mm / 2.5 mils PDF: 0.0762 mm / 3 mils Data Matrix: 0.152 mm / 6 mils  SAFETY & REGULATORY  Agency Approvals  The product meets necessary safety and regulatory a for its intended use.  Environmental Compliance  Complies to EU RoHS  SOFTWARE  DATALOGIC MOBILITY SUITE - Discover more on: datalogic.github.id			
Camera       Resolution: 13 MP; Illumination: LED flash; Lens: Aur         Scan Engine       2D Ultra slim area imager (supports 1D / 2D codes) Halogen™ DE2102-HP: Resolution: Megapixel (1280 x 800 pixels) Depth of Field: 4 to 90 cm / 1.6 to 35 in, depending or code density and type Aiming: 650nm VLD; Field of View: 42°H x 26°V         Minimum Element Width       Halogen™ DE2102-HP: 1D Linear: 0.0635 mm / 2.5 mils PDF: 0.0762 mm / 3 mils Data Matrix: 0.152 mm / 6 mils         SAFETY & REGULATORY         Agency Approvals       The product meets necessary safety and regulatory a for its intended use.         Environmental Compliance       Complies to EU RoHS         SOFTWARE         DATALOGIC MOBILITY SUITE - Discover more on: datalogic.github.id			
2D Ultra slim area imager (supports 1D / 2D codes) Halogen™ DE2102-HP: Resolution: Megapixel (1280 x 800 pixels) Depth of Field, 4 to 90 cm / 1.6 to 35 in, depending or code density and type Aiming: 650nm VLD; Field of View: 42°H x 26°V  Halogen™ DE2102-HP: 1D Linear: 0.0635 mm / 2.5 mils PDF: 0.0762 mm / 3 mils Data Matrix: 0.152 mm / 6 mils  SAFETY & REGULATORY  Agency Approvals  The product meets necessary safety and regulatory a for its intended use.  Environmental Compliance  Complies to EU RoHS  SOFTWARE  DATALOGIC MOBILITY SUITE - Discover more on: datalogic.github.id			
Halogen™ DE2102-HP: Resolution: Megapixel (1280 x 800 pixels) Depth of Field: 4 to 90 cm / 1.6 to 35 in, depending of code density and type Aiming: 650nm VLD; Field of View: 42°H x 26°V  Halogen™ DE2102-HP: 1D Linear: 0.0635 mm / 2.5 mils PDF: 0.0762 mm / 3 mils Data Matrix: 0.152 mm / 6 mils  SAFETY & REGULATORY  Agency Approvals  The product meets necessary safety and regulatory a for its intended use.  Environmental Compliance  Complies to EU RoHS  SOFTWARE  DATALOGIC MOBILITY SUITE - Discover more on: datalogic.github.id	n bar		
Minimum Element Width  10 Linear: 0.0635 mm / 2.5 mils PDF: 0.0762 mm / 3 mils Data Matrix: 0.152 mm / 6 mils  SAFETY & REGULATORY  Agency Approvals  The product meets necessary safety and regulatory a for its intended use.  Environmental Compliance  Complies to EU RoHS  SOFTWARE  DATALOGIC MOBILITY SUITE - Discover more on: datalogic.github.ice			
Agency Approvals The product meets necessary safety and regulatory a for its intended use.  Environmental Compliance Complies to EU RoHS  SOFTWARE  DATALOGIC MOBILITY SUITE - Discover more on: datalogic.github.id			
for its intended use.  Environmental Compliance Complies to EU RoHS  SOFTWARE  DATALOGIC MOBILITY SUITE - Discover more on: datalogic.github.id	SAFETY & REGULATORY		
SOFTWARE DATALOGIC MOBILITY SUITE - Discover more on: datalogic.github.id	approvals		
DATALOGIC MOBILITY SUITE - Discover more on: datalogic.github.id			
launcher - to lockdown device to kinsk mode. Enter	DATALOGIC MOBILITY SUITE - Discover more on: datalogic.github.io		
Protection Browser -to web-browse only to a set of of approved Integrity KIT - to safeguard HW interfaces			
Scan2Deploy Studio – to configure and stage devices OEMConfig – for UEM/EMM Compatibility, AE QR Code Enrollment – for easy EMM/UEM enrollr			
SDKs (Java, Kotlin, Xamarin, .NET MAUI JavaScript), Visual Formatter – a no-code platform for barcode fo Wedge – a configurable bar code scanning input meth	rmatting,		
SoftSpot – a draggable touch scanner trigger, Logger – to collect advanced device events log, WiFi collect WiFi data and statistics, Battery Manager – to from different charging policies Snap OCR, Keyboard Key Gesture Support	select		
Additional Features			
Provisioning  Android TM Zero Touch, Android Enterprise QR code Enrolment, NFC Bump, EMM Token Enrollment, DPC Enrollment			
SOTI Mobicontrol, Omnissa Workspace One, Microso 42Gears SureMDM, Ivanti Neurons, and any Android UEM/EMM (supporting OEM Config Technology)			
Terminal Emulator and PTT Compatibility Highlight  Ivanti Velocity, StayLinked Smart TE			
SYSTEM			
SIM Slots Memor 25K only: 1 Nano SIM			
Expansion Slots Micro-SD card slot: Compatible with Micro SD-HC caup to 512 GB; User-accessible	rds,		
Memory System RAM: 4 GB; eMMC Flash: 64 GB			
Microprocessor 2 GHz Octa-core			
Operating System Android 13 with GMS , upgradeable to Android 15			
Real-Time Clock Time and date stamping under software control			
WARRANTY			
Warranty 1-Year Factory Warranty			

## **ACCESSORIES**

### **Base Stations/Chargers**

94A150137 Single Slot Dock 94ACC0419 4 Slot Battery Charger





### **Cases/Hostlers**

94ACC0312 Belt Holster 94ACC0418 Rubber Boot





### **Miscellaneous**

94ACC0417 Hand-strap (5 pieces)

© 2020-2025 Datalogic S.p.A. and/or its affiliates. • All rights reserved. Without limiting the rights under copyright, no part of this documentation may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means, or for any purpose, without the express written permission of Datalogic S.p.A. and/or its affiliates. • Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. in many countries, including the U.S. and the E.U. • Memor is a trademark of Datalogic S.p.A. and/or its affiliates, registered in many countries, including the U.S. and the E.U. • Android is a trademark of Google Inc. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. • The Bluetooth word mark and logos are owned by Bluetooth SIG, Inc. and any use of such marks by Datalogic Group companies is under license. • All other trademarks and brands are property of their respective owners • Product specifications are subject to change without notice. • DS-MEMOR-K-EN Rev A 20250326