



## NLS-MT93

### PORTABLE DATA COLLECTOR

## FEATURES

### ○ Heavily Customized Android

The value-added features of the NLS-MT93 including application protection and admin tool, seek to shore up Android's data security.

### ○ Long Expected Battery Life

The NLS-MT93 is equipped with a 5000mAh battery that provides a full-shift battery life of up to 12 hours from a single charge. What's more, the battery is changeable which guarantees the all-day continue use of device.

### ○ Rugged Durability

The NLS-MT93's rugged housing is sealed to IP67 standards for protection against dust and water and withstands 1.5m drops to concrete.

### ○ Diverse Functionalities

The NLS-MT93 offers 1D/2D/BT/Wi-Fi/4G /GPS/Camera/NFC functionalities to meet different application needs. Equipped with Newland's self-developed high performance barcode reading engine, the NLS-MT93 can decode various barcodes and support OCR character recognition.



2D Barcode



1D Barcode



Android



GPS



WiFi  
Dual Band



Bluetooth



Drop



Touch

# NLS-MT93

## Performance

Processor		2.0GHz, octa-core 64-bit processor
Operating System		Android 11
Memory		4GB RAM, 64GB ROM
Symbologies	2D	Aztec, Composite, CS Code, Maxicode, Micro PDF, Micro QR, PDF 417, QR Code, Data Matrix, DotCode.
	1D	Code128, Code 49, Code 16K, (GS1128) UCC/EAN-128, AIM-128, EAN-8, EAN-13, UPC-E, UPC-A, ITF, ITF 6, ITF 14, Matrix 2 of 5, Industrial 25, Standard 2 of 5, Code39, ISSN, ISBN, CodaBar, Code93, Code 11, Plessey, MSI Plessey, RSS.
Depth of Field (Depend on Barcode and Environment)	EAN-13	70mm-610mm(13mil)
	Code39	120mm-290mm(5mil)
	PDF417	110mm-230mm(6.7mil)
	Data Matrix	110mm-260mm(10mil)
	QR Code	55mm-410mm(15mil)

## Physical/Electrical

Dimensions (L×W×H)	159(L) × 74(W) × 15.9(H) mm
Weight	277g (including battery)
Display	5.5" (720×1440), multi-point capacitive touch screen with Gorilla Glass
Keypad	7 keys(side keys included)
Notification	Vibrator, speaker and multi-color LEDs
Battery	3.85V, 5000mAh
GPS	GPS (AGPS), GLONASS, Beidou, Galileo
Camera	Front camera: 5 megapixels, Rear camera: 13 megapixels, auto focus, with LED flashlight
Expansion	Micro SD Card ( Maximum 256GB)
Interface	USB Type-C , charging contacts on the bottom
AC Adapter	Output: DC5V/7V/9V, 2A Input: AC100~240V, 50~60Hz

## Environmental

Operating Temperature	-20°C to 55°C (-4°F to 131°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Humidity	5% to 95% (non-condensing)
Static Discharge	±15 kV (Air discharge), ±8 kV (Direct discharge)
Drop	1.5m drops to concrete (for six sides, one drop per side)
Sealing	IP67

## NFC

13.56MHz RFID	ISO14443A/B, ISO15693, ISO18000-3, MIFARE, FeliCa RF, Kovio, NFC Forum Type 1-4 Tags
---------------	--

## Wireless

WLAN RADIO		Built-in 802.11 a/b/g/n/ac, support 2.4G and 5G dual frequency
WWAN RADIO	2G	850/900/1800/1900MHz
	3G	WCDMA (B1, B2, B5, B8); CDMA: 1X EVDO (BC0); TD-SCDMA: B34/B39
	4G	TDD-LTE (B34, B38, B39, B40, B41) FDD-LTE (B1, B2, B3, B5, B7, B8, B20, B28 a&b)
WPAN RADIO		Bluetooth 4.2 BLE backward compatibility

## Accessory (Optional)

Battery, AC adapter, cable, hand strap, protective case, protective film, charging cradle , 4-slot battery charging cradle

Specifications are subject to change without notice.

2023/02/28

Version: V1.1

### Newland AIDC

Add: No.1 Rujiang West Rd,  
Mawei, Fuzhou, Fujian 350001, China  
Tel: +86-591-83979500  
Fax: +86-591-83979216  
Email: info@nlscan.com  
Web: www.newlandaidc.com

### Asia Pacific

Taiwan:  
Add: 7F-6, No. 268, Liancheng Rd.,  
Jhonghe Dist. 235, New Taipei City,Taiwan  
Tel: +886 2 7731 5388  
Email: info@newland-id.com.tw

### Europe & Middle East

Add: Rolweg 25, 4104 AV Culemborg,  
The Netherlands  
Tel: +31 (0) 345 87 00 33  
Email: sales@newland-id.com  
Tech Support: tech-support@newland-id.com

### North America & Latin America

Add: 46559 Fremont Blvd.,  
Fremont, CA 94538, USA  
Tel: +1 510 490 3888  
Fax: +1 510 490 3887  
Email: info@nlscan.com