



## NLS-NVH300X-V2-DP

### HANDHELD INDUSTRIAL DPM BARCODE SCANNER

## FEATURES

### Excellent DPM Decoding Capability

Featuring the latest UIMG<sup>®</sup> decoding system, it enhances decoding success rates for complex barcodes, optimizing workflows and improving overall decoding efficiency. It also delivers exceptional decoding performance for DPM barcodes, including laser-etched and dot-peened markings.

### Advanced Illumination system

Provide white direct illumination, red and blue diffuse ring lights, rich lighting system can meet different materials (such as reflection), shape (curved surface), background and bar code color of all kinds of complex scanning code needs.

### AI Function and Intelligent Learning

Equipped with the latest AI-powered barcode positioning technology, the NLS-NVH300 improves decoding performance for low-contrast barcodes. Additionally, intelligent learning enables automatic parameter adjustments based on different scenarios.

### High Protection Industrial Structure Design

The NLS-NVH300, built into an IP64-sealed and can withstand repeated falls from 2.4 meters to the ground, with excellent reliability and stability.



2D Barcode



1D Barcode



NSet



RS232



USB



Drop

# NLS-NVH300X-V2-HDP

## Performance

Image Sensor		1920 × 1200 CMOS
Illumination		Direct: white light LEDs;
Aiming		Diffuse: Ring of red&blue LEDs;
		650nm laser diode
Symbolologies	2D	QR Code, PDF417, Micro QR, Data Matrix, AZTEC.
	1D	EAN-13,EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code128,Code93, ITF-6,ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2 of 5, Code 39
Resolution*		≥1.5mil
Product Type		NLS-NVH300-HDP
Typical Depth of Field*	Code 39 2mil	20mm-34mm
	Code 39 1.67mil	21mm-25mm
	Data Matrix 3.33mil	18mm-33mm
	QR Code 1.67mil	23mm-25mm
	QR Code 3mil	18mm-30mm
Motion Tolerance*		2m/s
Min. Symbol Contrast*		20%
Scan Angle**		Roll: 360°, Pitch: ±60°, Skew: ±55°
Field of View		Horizontal 33.6°, Vertical 21.4°

Interface	USB, RS232, Ethernet
-----------	----------------------

## Physical

		5VDC±5%
Rated Power Consumption		2250mW (typical)
Current@5VDC	operating(typical)	364mA
	operating(max.)	461mA
Dimensions		76.0(W) ×107.0(D) ×185.0(H) mm
Weight		245g
Notification		Beep, LED indicator, Vibrator

## Environmental

Operating Temperature		-20°C to 50°C(-4°F to 122°F)
Storage Temperature		-40°C to 70°C(-40°F to 158°F)
Humidity		5% to 95% (non-condensing)
ESD		±16 KV (air discharge); ±8 KV (direct discharge)
Drop		2.4m
Sealing		IP64
Certifications		FCC Part15 Class B, CE EMC Class B
Accessories	USB	Used to connect the NVH300 to a host device.
	Cable RS-232	Used to connect the NVH300 to a host device. Adapter: input 100-240V,Output 5VDC/1.5A
	Ethernet	Used to connect the NVH300 to a host device. Adapter: input 100-240V,Output 5VDC/1.5A

\*Test conditions: T=23°C; Illumination=300lux using incandescent lamp; sample printed barcodes made by Newland.

\*\*Test conditions: Scan Distance= (min. DOF + max. DOF)/2; T=23°C; Illumination=300lux using incandescent lamp;

2D: QR Code; 10 Bytes; Resolution=15mil; PCS=0.8.

Specifications are subject to change without notice.

Version: V1.0 2025/08/04

### Newland AIDC

Add: No.1 Rujiang West Rd.,  
Mawei, Fuzhou, Fujian 350001, China  
Tel: +86-591-83979500  
Fax: +86-591-83979216  
Email: info@newlandaidc.com  
Web: www.newlandaidc.com

### Asia Pacific

Add: 6 Raffles Quay #14-06  
Singapore 048582  
Email: info@newlandaidc.com

### Europe & Middle East

Add: Rolweg 25, 4104 AV Culemborg,  
The Netherlands  
Tel: +31 (0) 345 87 00 33  
Email: sales@newland-id.com  
Tech Support: tech-support@newland-id.com

### North America & Latin America

Add: 46559 Fremont Blvd.,  
Fremont, CA 94538, USA  
Tel: +1 510 490 3888  
Fax: +1 510 490 3887  
Email: info@newlandaidc.com