

VFD220 Customer Display



Introduction

One of the most reliable customer display from ALC sourcing give your cashier counter look more customer friendly. 2 lines fluorescent display show clearly the total payment to be pay by the customer and thanks you message for your customer. Default USB cable for easy plug and play to your POS counter. With factory default 3 segment pole allow you to adjust the height of display according to your need. Bright vacuum fluorescent display with tested long life spends give you the maximum return of investment for your cashier counter. Powerful firmware now supports 11 command modes included EPSON etc. our experience on source of customer display faulty have been handle with Power supply from 5V to 24V to preventing mindless use of improper power input.

Specification

Display Method	Vacuum Fluorescent Display (Blue-green)
Display characters	40(20 columns x 2 lines)
Brightness	500~1000 cd/m ²
Character font	5 x 7 dot matrix
Character type	95 Alphanumeric, 32 International Characters
Character size	5.5(H) x 9.2(W) mm
Dot Size (X x Y)	0.86 x 1.2mm
Download characters	9 characters
Panel Dimension	220(W) x 45(D) x 125(H)mm
Pole Dimension	Per support length: 140(L) x 34.5(Dia)mm
Base Dimension	205(W) x 106(D) x 33(H)mm
Viewing Angle	Max. 90°
Horizontal Rotation	Max. 355°
Weight	Approx. 980 grams
Commands Mode	LD220, EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL
Language Support	FRANCE、GERMANY、U.K、DENMARKI、SWEDEN、ITALY、SPAIN、JAPAN、NORWAY、DENMARKII、SLAVONIC、RUSSIA、Portuguese、Canadian French、Nordic、Turkish、Greek、West European Latin
Interface	USB
Baud rate	Direct connection 9600 or 19,200 bps
MTBF	30,000 hours
Consumption	5-24 VDC
EMC standards	FCC, CE
Safety standards	
Support	OPOS/JPOS driver is standard.