



MioWORK™ L1000 Series

DOCKING STATION

Sold separately (Power Adapter included) - PN: TBD

- ▶ CHARGING STATUS LED**
 Indicated charging status of tablet and spare battery separately
- ▶ BATTERY CHARGING SLOT**
 Charge spare hot-swap battery
- ▶ USB TYPE-C 2.0 (HOST)**
 Connect to USB peripheral
- ▶ RJ45 LAN**
 For Ethernet data transfer when tablet is docked
- ▶ USB TYPE-A 2.0 (HOST)**
 Connect to USB peripheral
- ▶ DC-IN (12V)**
 Charging via power adapter
- ▶ LIQUID DRAINAGE DESIGN**
 Open sides and sloped design ensure liquids are not retained in the cradle base
- ▶ 10-PIN POGO CONNECTOR FOR DATA SYNC AND CHARGING**
 Durable for increased reliability

Specifications

Physical Interface	10-pin pogo pin connector (charging/data)
	USB Type-C 2.0 (host) x1, USB Type A 2.0 (host) x1
	RJ45 LAN x1
	Power DC jack
	Battery charging slot
Power Interface	12V power input
LED Indicator	Power input (green) x1, battery charging status (orange / green) x1
Mechanical Design	Liquid drainage feature
Environment	Temperature: -10° to +50°C (14° to +122°F) operating; -20° to +70°C (-4° to +158°F) storage Humidity: 0 ~ 95%, non-condensing
Certifications	CE/CB, FCC/IC, ROHS, WEEE
Weight	TBD
Dimensions	TBD