
## POINT-OF-SALE PRINTER TM-T82





An efficient business begins with Epson's TM-T82. With Epson's advanced printing technology, discover reliability and functionality that ensures an easy printing solution for all users. Designed with an adaptable mounting capability, the TM-T82 allows for versatile placement even in the smallest environment. Make the TM-T82 the perfect companion for your business today.





# **ENGINEERED FOR BUSINESS**

Unrivalled Performance With a MCBF of 60 million lines and an auto-cutter life of 1.5 million cuts.

**Ease-of-use** Features drop-in paper loading, auto-cutter and status LEDs. **All-in-one Box Convenience** Includes all necessary drivers and accessories for quick set-up.

## **SPECIFICATIONS** TM-T82



MODEL NUMBER	TM-T82
Printing Method	Thermal line printing
Print Font	
Font	9 × 17 / 12 × 24, Hanji Font: 24 × 24, Thai Font: 9 × 24 / 12 × 24
Character Size (W x H)	0.88 × 2.13 mm / 1.25 × 3 mm, Hanji font: 3 × 3 mm, Thai font: 0.88 × 3 mm / 1.25 × 3 mm
Character Set	95 Alphanumeric, 18 set International, 128 × 43 pages (including user-defined page) Hanzi: Simplified Chinese: GB18030-2000: 28,553 Bar code: UPC-A, UPC-E, JAN13(EAN13), JAN8(EAN), CODE39, ITF, CODABAR(NW-7), CODE93, CODE128, GS1-128, GS1 DataBar Two-dimensional code: PDF417, QRCode, MaxiCode, 2D GS1 DataBar, Composite Symbology
Characters Per Inch	
Interface	Built-in USB + UIB (Serial or Parallel interface), Ethernet interface
Receive Data Buffer	4KB or 45 bytes
Print Speed	Max 150mm/s
Dot Density	203 x 203 dpi
Paper	
Roll Paper Width and Roll Diameter	79.5 ± 0.5 (W) × dia. 83.0 57.5 ± 0.5 (W) × dia. 83.0
Power	
Supply Voltage	DC +24V ± 7%
Power Consumption	
Operating	Approx. 1.5A (Mean / Print ratio 18% with print pattern)
Standby	Approx. 0.1A (Mean)
Power Supply	External power supply (Model: PS-180)
Reliability	
Printer Mechanism Life	15 million lines
Auto Cutter Life	1.5 million cuts
MTBF	360,000 hours
MCBF	60,000,000 lines
Overall Dimensions (D x W x H)	140 × 199 × 146 mm
Mass	Approx. 1.7kg
EMI and Safety Standards	Oceania EMI AS/NZS CSPR22 Class A
Option	External buzzer unit
Standard Accessories ROM	Roll paper × 1 roll (for checking the initial movement of the printer),   CD-ROM (Drivers, Utility Software, Manuals),   Setup guide, Power button cover, Waterproof power button cover,   Wall hanging bracket, Screws for wall hanging bracket,   Rubber feet for vertical installation, Control panel sheet for vertical installation,   58-mm width paper guide, External power supply (Model: PS-180)
Installation	Horizontally / vertically / vertically with wall hanging bracket / wall hanging

### ensions & Weight

**ght:** Approx. 1.7 kg (3.74lbs)



#### end

dots per 25.4 mm (dots per inch)

characters per 25.4 mm (characters per inch)

14 Epson Singapore Pte Ltd. All Rights erved. Reproduction in part or in whole, out the written permission from Epson, is tly prohibited.

ON and EXCEED YOUR VISION are stered trademarks of Seiko Epson poration.

ther product names and other company les used herein are for identification purposes and are the trademarks or registered emarks of their respective owners.

on disclaims any and all rights in those marks. on disclarits any and an ingris in troose frances t samples shown herein are simulations. actual product design and contents may . Specifications are subject to change out notice and may vary between countries. se check with local Epson offices for more mation.

Information correct as at March 2014