POINT-OF-SALE PRINTER
TM-T88V

EPSON
EXCEED YOUR VISION

HIGHEST PRODUCTIVITY FOR THE MOST EFFICIENT CHECKOUT.

Epson's TM-T88V is the high-speed thermal receipt printer with a compact design and fastest printing performance, a powerful successor to the TM-T88IV. Delivering best-in-class reliability, print options that reduce paper usage up to 30% and blazing printing speeds of up to 300mm/second, it's ideal for high-volume environments requiring fast and quiet printing. With ease-of-use features and dual interfaces, the TM-T88V promises greater flexibility, making it the best performing printer to suit your business needs.

Wall Mount	Compact	Print	Auto Cutter	Cost Effective

IT'S IN THE DETAILS.

Unprecedented Reliability
MCBF of 70 million lines and an auto-cutter life of 2 million cuts.

High Resolution Printing
Increase productivity with 16 levels of grayscale, an industry-first that ensures clear and crisp graphics.

Ease of Maintenance
Convenient drop-in paper loading and an enhanced paper cover design for spill resistance.

EPSON
EXCEED YOUR VISION

MODEL NUMBER		TM-T88V
Printing Method		Thermal line printing
Print Font		
Font		9 × 17 / 12 × 24
Column Capacity		56 / 42 columns
Character Size (W x H)		0.99 × 2.4 mm / 1.41 × 3.39 mm
Character Set		95 Alphanumeric, 18 set International, 128 × 43 Graphic
		Barcode: UPC-A, UPC-E, JAN8(EAN), JAN13(EAN), CODE39, CODE93, CODE128, ITF, CODABAR, GS1-128, GS1 DataBar
		Two-dimensional Code: PDF417, QRCode, MaxiCode, 2D GS1 DataBar, Composite Symbology
		South Asian models carry Thai (128 x 3), Vietnamese (128 x 2) characters,
		Simplified Chinese (GB18030-2000:28,553)
Character Structure		12 x 24 / 9 x 17 / 9 x 24 (including 2-dot spacing horizontally)
Interface		Built-in USB + UIB (Serial or Parallel or Ethernet Interface)
Data Buffer		4KB or 45 bytes
Print Speed		Max. 300mm/sec.
Dot Density		180 x 180 dpi*
Paper		
Roll paper	Width x Diameter	79.5 ± 0.5 mm × 83.0 / 57.5 ± 0.5 × 83.0 mm
	Thickness	0.06 to 0.07 mm
Power		
Supply Voltage		24 VDC ± 7 %
Power Consumption		Approx. 1.8A (Mean)
D.K.D. Function		2 Drivers
Reliability		
Printer Mechanism Life		20 million lines
Auto Cutter Life		2 million cuts (when using OJI Paper PD150R or PD160R)
MTBF		360,000 hours
MCBF		70 million lines
Overall Dimensions (D x W x H)		195 × 145 × 148 mm
Weight		Approx. 1.6kg
EMC & Safety Standards		UL / FCC, CE Marking, AS / NZS CISPR22 Class A
Power Supply (option)		PS-180
Option		Wall-hanging Bracket WH-10

*dots per 25.4mm (dots per inch)

Selected models are equipped with a buzzer feature that sounds with each new receipt.

Dimensions & Weight
Weight: Approx. 1.6kg (3.52lbs)

148mm
(5.83")

195mm
(7.68")

145mm
(5.7")

Information correct as at February 2019