



**EMPOWER SERVICE WITH  
 ADVANCED CONNECTIVITY.**

Epson's TM-T88VI offers fast print speeds and flexible connectivity that is vital in demanding environments. Equipped with state-of-the-art technology, the TM-T88VI allows you to enjoy the benefits of web and POS services while maintaining compatibility with existing applications or set-ups. Through connectivity features including cloud service and Near-Field Communication (NFC), efficiency is enhanced for excellent customer service. Experience greater cost-savings with low power consumption and advanced paper saving capabilities. In addition, the TM-T88VI's intelligent counterpart, TM-T88VI-iHub, offers peripheral support and control on top of similar wireless connectivity. Designed with details, grow your business with this series.



-   
Designed for Cloud
-   
Mobility
-   
Wall Mount
-   
Auto Cutter

**IT'S IN THE DETAILS.**

**Cloud Accessibility**

Retrieve information and print directly from cloud without a separate connection platform.

**Flexible Connectivity**

Customise your set-up with versatile communication, \*triple interfaces and \*\*peripheral support. Pair your device instantly using NFC, QR code or iBeacon.

**Eco-Efficient Business Operations**

Encourage a pro-environmental business setting with its industry-leading low power consumption capabilities and advanced paper-saving function.

\* Applicable for TM-T88VI only.  
 \*\* Applicable for TM-T88VI-iHub only.  
 • Peripheral connection support applicable for TM-T88VI-iHub only.

MODEL NUMBER	TM-T88VI	TM-T88VI-iHub
<b>Print Method</b>	Thermal line printing	
<b>Print Font</b>		
Font	9 x 17 / 12 x 24	
Column Capacity	56 / 42 columns	
Character Size (W x H)	0.99 x 2.4 mm / 1.41 x 3.39 mm	
Character Set	95 Alphanumeric, 18 International, 128 x 43 Graphics	
Character Structure	12 x 24 / 9 x 17 / 9 x 24	
<b>Interface</b>	Built-in USB (Type A for OT-WL02 or DM-D30 / DM-D110) + Built-in USB (Type B) + Built-in Ethernet + UIB (Serial or Parallel)	Built-in USB (3 * Type A for OT-WL02, DM-D30 / DM-D110 or other POS Peripherals) + Built-in USB (Type B) + Built-in Ethernet + Serial (POS Peripheral) + USB Charging Port (0.5A-2.1A)
<b>Data Buffer</b>		
Receive	45 bytes or 4 KB, selectable	
User-defined	12 KB	
Macro	2 KB	
NV Graphics	384 KB	
NV User	1 KB	
<b>Print Speed</b>	Max. 350 mm/sec.	
<b>Dot Density</b>	180 x 180 dpi*	
<b>Paper</b>		
Width x Diameter	79.5 ± 0.5 mm x 83.0 / 57.5 ± 0.5 x 83.0 mm	
Thickness	0.048 mm to 0.08 mm	
<b>Power Saving</b>		
Supply Voltage	DC +24 V ± 7%	
Power Consumption	Approx. 27.6 W	Approx. 27.4 W
Power Supply	PS-180	Adapter V
<b>Reliability</b>		
Printer Mechanism Life	20 million lines	
Auto Cutter Life	3 million cuts	
MTBF	360,000 hours	350,000 hours
MCBF	70 million lines	
<b>Colour</b>	Black (EBCK), White (ENN8.5)	Black (EBCK)
<b>Overall Dimensions (W x D x H)</b>	145 x 195 x 148 mm	
<b>Mass</b>	Approx. 1.6 kg	
<b>EMI</b>	FCC Class A, ICES-003 Class A	
<b>Safety Standard</b>	UL60950-1/CSA C22.2 No.60950-1	
<b>Option</b>		
Wireless LAN	OT-WL02 (ELPAP10)	
Customer Display Unit	DM-D30, DM-D110	
Wall Hanging Unit	WH-10	-
External Buzzer	OT-BZ20	
<b>Printer Hardware</b>		
CPU	ARM Cortex-A5 384 MHz	
Web Content Memory	30 MB	100 MB
<b>Printer Software</b>		
Device Control Software	ESC/POS, ePOS-Print XML, ePOS-SDK	
Web Server	lighttpd/php/sqlite3	
Printer Driver	ePOS-Print SDK, Windows Driver (APD), OPOS, OPOS.NET, JavaPOS (Windows), JavaPOS (Linux), TM Virtual Port Driver, CUPS Driver (Linux), Mac Driver	
Utility	TM-T88VI Utility, TM Utility (iOS/Android), EpsonNet Config, EpsonNet Config (Web version: for network setting) TM Print Assistant	
<b>Easy Setting</b>	Easy pairing with NFC, QR Code, iBeacon**	



**Dimensions & Weight**

**TM-T88VI**

**Weight:** Approx. 1.6 kg (3.53 lb)

**TM-T88VI-iHub**

**Weight:** Approx. 1.6 kg (3.53 lb)



© 2018 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Information correct as at August 2018

\*dots per 25.4mm (dots per inch)

\*\*specific iBeacon dongle is required (BT820)