

Tousei TS-M420 Label Printer

Details of Thermal Label Printer

Specifications	
Print Method	Direct Line Thermal
Interfaces	USB / LAN / Bluetooth
Print Comand	TSPL(CPCL/ESC/POS compatible)
Pirnt Speed	Max to 160mm/s
Resolution	203DPI (8dot/mm)
Media Sensor	Transmissive and Reflective
Logo	support downloading and printing logo
Supported Font:	ASCII Font: 8*12, 9*17, 12*20, 12*24, 14*10, 14*25, 16*24, 21*27,24*32, 32*48 GB18030 font: 24*24 BIG5 Font: 24*24
Supported Code:	1D: UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128 2D: QR CODE,PDF417
Driver	Win2003 / WinXP / Win7 / WIN8 / WIN10 / MACOS ; Support IOS / Android
Power	24V/2.5A DC charger
TPH Reliability	about 50km or 100millions pulses
Paper	
Paper Types	continuous paper, label paper, folded paper, tag paper
Max paper roll	110*100mm (width*diameter)
Print Width	100mm (Max 800 points)
Paper Thickness	0.06-0.30 mm
Package	
Printer Dimension	226*180*147mm
Printer N.W.	1200g
Package	1pc with accessories/box, 8boxes/ctn
Accessories	Manual, CD driver, USB Cable,Adapter, Power line
Box Dimension	292*196*162mm
Box G.W.	2Kgs
CTN Dimension	60 x 39.6 x 34.4 cm
CTN G.W.	17kgs
Environmental	
Working Temperature	+0 ℃ ~ 50 ℃ (no condensation)
Working Humidity	20% ~ 85% RH (no condensation)
Storage Temperature	-20 ℃ ~ 60 ℃ (no condensation)
Storage Humidity	5% ~ 95% RH (no condensation)
Mechanical Noise	less than 60dB

