

VPOS



VPT3-i3

15" All in One Touch POS Terminal

Features

- Industrial Grade Aluminium casing
- True Bezel Free Designing
- High Performance 15inch LED Panel (1024*768)
- Cost effective: Outstanding performance at a competitive pricing



COM2



LINE



MIC



LAN



USB



USB



USB



USB



USB



USB



VGA



HDMI



DC



USB



USB



USB



USB



USB



USB



USB



USB



USB



USB



USB

VPT3-i3

15" All in One Touch POS Terminal

Specifications

Type	15" All In One Touch POS terminal
Colour	Black
Material	Magaluma
Optional	WIFI MSR VFD/LED8/Second display
Motherboard part	
Main Board	ITX-TD
CPU	Intel® 8th Generation Core™ i3 Processors
BIOS	AMI BIOS
RAM Support	8GB
Storage	M.2 M-Key 128G
Network Support	Realtek 8111H Gigabit Ethernet
Audio	Support
Main display part	
LCD Size	15" LED-LCD
View Angle	left/right +80°~ -80° up/down +70°~ -70°
Brightness	350cd /m²
Resolution	XGA 1024×768 @ 60Hz
Touch Screen	
Type	Capacitive Touch Screen (Glass and Glass) (ILI)
Touch interface	USB
Type	12" second display
Resolution	XGA 1024×768 @ 60Hz
I/O Part	
I/O port	DC IN*1(DC5525) HDMI*1 VGA*1 POWER BUTTON*1 BLK UP*1 BLK DOWN*1 COM*1(DB9) USB2.0&USB3.0 *6 LAN*1 MIC_IN *1 LINE_OUT*1
Rotation	70
Power Consumption	50W(MAX) DC 12V
Operating Temperature	0°C to 40°C
Storage Temperature	-20°C to 60°C
Accessory	Power adaptor (DC5525), power cable, CD for driver