



WP-Q2A

Mobile Receipt & Label Printer

- Print width:48mm
- Maximum roll diameter:50mm
- Printing speed:Min 50.8mm/s,Max 101mm/s
- Support thermal paper / thermal adhesive paper
- Compatible with WINDOWS/Android/IOS systems


 Police Service	 Supermarket
 Catering	 Logistics





WP-Q2A

Mobile Receipt & Label Printer



Printing	Label print mode	Receipt print mode
Printing method	Direct Thermal	
Resolution	203 DPI	
Print width	Max.48 mm	
Printing speed	Min. 50.8 mm/s, Max. 101 mm/s	90mm/s
Media		
Media type	Thermal paper roll /Thermal adhesive paper	Thermal paper
Media width	20~60 mm	58 mm
Media external diameter	50 mm	
Paper out method	Tearing-off	
Performance Features		
Print head temperature detection	Thermistor	
Cover open detection	Micro Switch	
Media detection	Photoelectric Sensors	
Interface	USB / USB+Bluetooth	
Storage	Flash 576 kb	
Fonts / Graphics / Symbologies		
Character	Font 0 to Font8	Font A: 12x24, Font B: 9x17, CHN: 24*24
1D barcode	CODE128/EAN128/ITF/Interleaved Two of Five/CODE39/CODE39C/CODE39S/CODE93/EAN13/EAN13+2/EAN13+5/EAN8/ EAN8+2/EAN8+5/CODABAR/POSTNET/UPC-A/UPCA+2/UPCA+5/UPCE/UPCE+2/UPCE+5/MSI/MSIC/PLESSEY/ITF14/EAN14	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128
2D bar code	QR CODE	
Rotation	0°; 90°; 180°; 270°	
Physical Features		
Dimension	122.28 * 93.99 * 60.07mm(D*W*H)	
Weight	0.343 kg	
Software		
Driver	WINDOWS / Android / IOS	
Power supply		
Battery	DC 7.2V/2500MAH	
Charging input	Standard USB cable charging: 5V / 2A Optional DC adapter charging: 9V / 2A	
Environmental Condi		
Operation	0~45 °C Humidity; RH:10 ~ 80%	
Storage environment	-10~60 °C , ≤93% RH (40°C) no condensing	



Guangzhou Winprt Technology Co., Ltd.
Address: Room 614, NO.80 JinGang Road,
Nansha District, Guangzhou, Guangdong, China.
<http://www.winprt.com>
Email:overseas@winprt.com

