



WP-Q3A Thermal Receipt & Label Printer

- Dual mode bluetooth
- OLED screen available
- Long lasting battery life
- Support direct USB charging
- Compatible with TSPL,EPL,ZPL,DPL,CPCL,ESC/POS



Store



Hospital



Café



Logistics





WP-Q3A

Thermal Receipt & Label Printer



Printing Features	WP-Q3A
Printing method	Direct Thermal
Resolution	203 DPI
Max.print speed	Max. 70mm (2.7") /s
Max.print width	72 mm (2.8")
Max.print length	1778 mm (70")
Media	
Media type	Continuous, gap, black mark
Media width	20 mm~76 mm
Label roll diameter	50 mm
Performance Features	
Processor	32-bit CPU
Memory	8MB Flash Memory / 8MB SDRAM/MicroSD
Interface	USB+Bluetooth ; USB+WIFI
Screen	OLED (1.3") Resolution:128*64 pix
Fonts/Graphics/Symbologies	
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software
1D bar code	Code 39,Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST
2D bar code	PDF-417, Maxicode, DataMatrix, QR code,Aztec
Emulation	TSPL;EPL;ZPL;DPL;CPCL;ESC/POS
Physical Features	
Dimension	124*108*61mm(D*W*H)
Weight	0.357 KG
Reliability	
Printer head life	30 KM
Software	
Operation system	Windows/Android/IOS
SDK	Windows/Android/IOS
Power supply	
Output	DC 9V/2A
Battery life	7.4V/2500mAh

www.alcaidc.com

