



Mobile Receipt & Label Printer

XP-P301A



Key features

- Multiple 1D barcode printing
- QR CODE / PDF 417 2D barcode printing
- NV LOGO download picture printing
- Compatible with Windows/Linux/Android/iOS systems
- Multiple languages available.

Applications



Shopping



Mart



Restaurant



Hospital



Coffee Shop



Ticketing

Model	XP-P301A	
Printing method	Direct Thermal	
Emulation	ESC/POS	TSPL
Resolution	203 DPI	
Max.print speed	70 mm/s	
Max.print width	72 mm	
Printing specifications	/	
Storage	Memory:128KB / FLASH:512 KB+8MB	
Monitor	0.96", 128×64 OLED	
Button	Power button, Feed button	

Media		
Media type	Continuous paper, label paper, black label paper	
Media width	25~80mm	
Paper thickness	0.06~0.14mm	
Media roll diameter	50 mm	
Paper exit method	Tearing off	

Fonts/Graphics/Symbologies		
Character size	Simplified Chinese (GB18030): 24 × 24, Traditional Chinese (BIG5): 24 × 24, Japanese (SHIFT-JIS): 24 × 24, Korean (KSC5601): 24 × 24, English characters FONTA: 12 × 24, English Character FONTB: 9 × 17	
1D bar code	UPC-A/UPC-E/JAN13 (EAN13) / JAN8(EAN8)/CODE39/ITF/CODABAR/ CODE93/CODE128	CODE128, EAN128, ITF, CODE25, CODE39, CODE39C, CODE39S, CODE93, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR, POSTNET, UPC-A, UPCA+2, UPCA+5, UPCE, UPCE+2, UPCE+5, MSI, MSIC, PLESSEY, ITF14, EAN14
2D bar code	QR CODE / PDF417	
Character enlargement/rotation	Magnify 1-8 times, rotate (0°C, 90°C, 180°C, 270°C)	

Physical Features	
Dimension	123 × 110 × 62mm(D×W×H)
Weight	340g
Operation	6~40 °C, Humidity: RH 20 ~ 90%
Storage environment	-25 ~ 55 °C, Humidity: RH 20 ~ 93%
Power Input	DC 5V / 2A
Battery	DC 7.2V / 2550mAh
Charging time	3 hour, 58min
Standby time	95 hour, 48min
Printing battery life	3 hour, 47min
Operating system	WINDOWS/ Android / IOS / Linux



Scan QR code to checkout Xprinter website for more update information.
 Phone: (+86 756) 3932 978
 Http://www.xprintertech.com
 Email: overseas@xprinter.net

