

GRANIT™ ULTRA 2100i

Ultra-Rugged Corded Area-Imaging Scanner

Granit Ultra scanners expand capabilities and define the next generation of ultra-rugged scanning.

ULTRA SCAN PERFORMANCE

For a scanner to optimize productivity, it should read and transmit common barcodes nearly as fast as the user can pull the trigger, and Granit Ultra is engineered to do just that. Granit Ultra with AI drives 45% faster scanning¹ for improved productivity.

ULTRA DURABILITY

In modern warehouse, distribution center, and manufacturing environments, any scanner must be durable enough to survive harsh operating conditions. Under exactly that kind of rough treatment, Honeywell Granit Ultra is ready to deliver.

ULTRA EASE OF USE

Ready to operate right out of the box for many applications, Granit offers easy custom configuration in the time it takes to scan a barcode. For further workflow improvement, Granit can also read multiple codes in the field of view, organizing and outputting the data in a predefined order using Honeywell's Data Format Editor.



Honeywell Granit Ultra 2100i
Ultra-Rugged Scanner

SCAN MODELS

- SR (Standard Range) models are ready to read barcodes from contact to arms length
- HD (High-Density) models are ready to read high-density codes as small as 2mil 1D/2D codes.
- XR (Expanded Range) models are ready to read UPC/EAN13 from contact to nearly 6' (1.8m), or up to 33' (10.85m) for 100 mil Code 39
- XLR (Ultra Long Range) models are ready to read barcodes up to 98' (30m) for 100mil Code 39

FEATURES AND BENEFITS



Built to survive harsh treatment including 3m (10ft) drops, 7500 1m (3.3ft) tumbles, operating temperatures from -30°C to 50°C (-22°F to 122°F), and IP65/68 sealing, Granit Ultra reduces service costs and increases device uptime



Granit Ultra provides rapid scanning, even on damaged and low quality barcodes. High quality barcodes transmit faster than ever.



SR model reads from contact to arms length. HD model reads high-density codes down to 2mil 2D codes. XR model is ideally suited to near and mid-field scanning operations on 1D and 2D barcodes. The XLR model is designed for ultra long range barcode reading.



The Honeywell Scanner Management Utility (SMU) creates a holistic solution that automates how you deploy and update the scanners in your environment.

Honeywell

Granit Ultra 2100i Technical Specifications

MECHANICAL

Scanner dimensions (L x W x H): 194.8mm x 75.8mm x 139.5mm (7.7 in x 3.0 in x 5.5 in)
Scanner Weight: 330g (11.64 oz)
User Indicators: Good decode LEDs, Beeper (adjustable tone and volume), Vibration (adjustable)

ELECTRICAL

Input Voltage: 4.0 VDC to 5.5 VDC
Operating Power: 2.15W (430mA @ 5VDC)
Standby Power: 0.875W (175mA @ 5VDC)
Host System Interfaces:
USB, Keyboard Wedge, RS-232 TTL
(cables available to convert for +/-12V True use)

ENVIRONMENTAL

Operating Temperature: -30°C to 50°C (-22°F to 122°F)
Storage Temperature: -40°C to 70°C (-40°F to 158°F)
Humidity: Up to 95% relative humidity, non-condensing
Drop:
3m (10 ft): MIL-STD-810G, 25°C (77°F), 55% relative humidity
2.5m (8.2 ft): 20 drops from -30°C to 50°C (-22°F to 122°F), 55% relative humidity
2m (6.5 ft): 50 drops from -30°C to 50°C (-22°F to 122°F), uncontrolled relative humidity
Tumble: 7,500 1m (3.3ft) tumbles
Vibration: Withstands 5G peak from 5 to 300Hz
Trigger activations: Tested to 3 million cycles

Environmental Sealing: IP65 and IP68
Light Levels: 0 to 100,000 lux (9,290 foot-candles)
ESD: +/-20KV air discharge, +/-8kV contact discharge, +/-8kV indirect coupling plane

SCAN PERFORMANCE

Scan Pattern -SR/HD: Area imager (1280x1080 pixel array)
Scan Pattern -XR: Near and Far: Area imager (1280x1080 pixel array)
Scan Pattern -XLR: Near and Far: Area Imager (1920x800 pixel array)
Illumination -SR/HD: Warm White 2700K LED
Illumination -XR/XLR: Yellow-Green LED
Aimer -SR/HD: Green LED, 525nm peak wavelength
Aimer -XR/XLR: Green class 2 laser, 520nm peak wavelength
Motion Tolerance: Up to 4000 mm/s
Scan Angle (Field of View):
HD: Horizontal 28°, Vertical 24°
SR: Horizontal: 42°, Vertical 36°
XR-Near: Horizontal 42°, Vertical 36°
XR-Far: Horizontal 16°, Vertical 14°
XLR-Near: Horizontal: 45°, Vertical 19.6°
XLR-Far: Horizontal 13.7°, Vertical 5.7°
Print Contrast: As low as 15%
Roll, Pitch, Skew: +/-360°, +/-65°, +/-65°
Minimum Barcode Resolution:
SR/XR/XLR: 2.5mil 1D, 5mil 2D
HD: 2mil 1D, 2mil 2D
Image Capture: Up to 109PPI on an A4 document

Decode Capabilities^{2:}

1D: Code 39, code 128, code 93, code 11, code 32
Pharmaceutical, EAN, UPC, codabar, China Post, GS1 databar
2D: Aztec, Data Matrix, QR/Micro QR code, Maxicode, Chinese sensible (Han Xin) code, postal code, PDF417, DotCode,
Digital Watermarking: Digimarc
OCR: OCR A, OCR B, MICR E-13B and SEMI Font, in a 6 to 60 point OCR typeface
Note: Decode capabilities dependent on configuration.

REGULATORY^{3:}

EMC: EN55032, EN55035, EN61000-3-2, EN61000-3-3, FCC Part 15 Subpart B, ICES-003 Issue 7
Safety, Health and Environmental Compliance:
EN62368-1, IEC 62368-1, IEC62471, IEC-63000(ROHS), UL 62368-1, CSA C22.2 NO. 62368-1, IEC60825 for XR and XLR models (laser)

Accessories: Stands, holders, holsters, power supplies, cables, heaters.

Warranty: Three-year factory warranty
Services: Honeywell Edge Service
Utilities and Management: EZConfig, SMU, Total Freedom, Scanner Edge, SDKs, Various Drivers

SYMBOLGY ⁴	STANDARD RANGE(SR) - TYPICAL		EXPANDED RANGE(XR) - TYPICAL		ULTRA LONG RANGE (XLR) - TYPICAL		HIGH-DENSITY(HD) - TYPICAL	
	NEAR DISTANCE (MM [IN])	FAR DISTANCE (MM [IN])	NEAR DISTANCE (MM [IN])	FAR DISTANCE (MM [IN])	NEAR DISTANCE (MM [IN])	FAR DISTANCE (MM [IN])	NEAR DISTANCE (MM [IN])	FAR DISTANCE (MM [IN])
2mil C39	-	-	-	-	-	-	0 [0.0]	72 [2.83]
5 mil C39	10 [0.39]	269 [10.59]	10 [0.39]	269 [10.59]	82 [3.23]	1,665 [65.55]	0 [0.0]	123 [4.84]
10 mil C128	0 [0.0]	531 [20.91]	0 [0.0]	1,503 [59.17]	43 [1.69]	3,032 [119.37]	0 [0.0]	147 [5.79]
13 mil UPC	0 [0.0]	634 [24.96]	0 [0.0]	1,780 [70.08]	19 [0.75]	3,679 [144.84]	18 [0.71]	155 [6.10]
20 mil C128	0 [0.0]	1,033 [40.67]	0 [0.0]	2,812 [110.71]	-	7,504 [295.43]	-	-
100 mil C39	-	-	-	10,848 [427.09]	-	29,918 [1,177]	-	-
5mil DataMatrix	-	-	-	-	-	-	0 [0.0]	84 [3.31]
10 mil DataMatrix	5 [0.20]	261 [10.28]	5 [0.20]	261 [10.28]	90 [3.54]	1,566 [61.26]	0 [0.0]	116 [4.57]
100 mil DataMatrix	-	-	-	5,329 [209.80]	-	15,029 [591.69]	-	-
20 mil QR Code	0 [0.0]	480 [18.9]	0 [0.0]	1,464 [57.64]	*	*	0 [0.0]	172 [6.77]

* Comparable to 10mil C128 decoding range

- Honeywell standard benchmarking testing conducted on Granit Ultra vs. Granit XP on 6 collections of reference barcodes. Granit Ultra integrates high speed processing, AI(Artificial Intelligence) algorithms, and decoding enhancements to result in an average 45% scanning speed increase vs. Granit XP, enabling improved productivity.
- For a complete listing of all supported barcode symbologies, please visit <http://honeywell.com/PSS-symbologies>.
- For a complete listing of all compliance approvals and certifications, please visit www.honeywell.com/PSScompliance.
- Performance may be impacted by barcode quality and environmental conditions

For more information

automation.honeywell.com

Honeywell Industrial Automation

855 S Mint St
Charlotte, NC 28202
800-582-4263
www.honeywell.com

Granit™ is trademark or registered trademark of Honeywell International Inc. All other trademarks are the property of their respective owners.

Granit Ultra 2100i Datasheet | Rev C | 02/26
© 2026 Honeywell International Inc.

