

Features

- Powered by USB (No external power supply required)
- Dual and Three track capability
- Bi-directional read capability
- Reads encoded cards that meet ISO, ANSI, and AAMVA standards
- Up to 1,000,000 passes with ISO-conforming cards
- Includes USB interface
- Dual color LED



General Info **Color:** White, Black

Dimensions: Height: 1.23 in (31,3 mm), Width: 1.28 in (32,5 mm), Length: 3.94 in (100 mm)

Weight: lbs (oz) Interface USB

Reference Standards ISO, ANSI, CDL, AAMVA

Power Input From USB

Recording Method Two-frequency coherent phase (F2F)

Message Format
-Keyboard
-Human Interface Device (HID)

Card Speed 3 - 50 i.p.s.

Card Types ISO, ANSI, AAMVA (drivers license)

MTBF
Electronics: 125,000 hours
Head: 1,000,000 passes

Environment

Temperature
Operating: 32°F - 131°F (0°C - 55°C)
Storage: -22°F - 158°F (-30°C - 70°C)

Humidity
Operating: Operating: 10% - 90% non-condensing
Storage: 0% - 100% non-condensing

Altitude
Operating: 0 - 10,000 ft (0 - 3,048 m)
Storage: 0 - 50,000 ft (0 - 15,240 m)

Standard Configurations

Keyboard Emulation Software Interface

Note: Data is sent as if it were a USB keyboard. Read data can be viewed in applications such as Windows® Notepad without requiring additional drivers or application programming

Description	Part Number
Tracks 1, 2, White	21040109
Tracks 1, 2, Black	21040110
Tracks 1, 2, 3, White	21040107
Tracks 1, 2, 3, Black	21040108